

SPECIAL SECTION

Multilevel Converters

P. BAUER, M.P. KAZMIERKOWSKI, and R. STRZELECKI

The area of power electronics and controlled drives is a major and important discipline in electrical engineering. Power electronics, which basically deals with high efficiency conversion and control of electrical energy, has found various applications, such as: DC and AC machine drives, active harmonic filtering, induction heating, AC and DC power supply, active and reactive power flow control, high-voltage direct-current (HVDC) energy systems and flexible AC transmission systems (FACTS), coupling of energy storages in distributed generation (DG) and smart grid (SG) systems, solid state transformers (SST), contactless energy transfer, etc. [1–3]. Therefore, appreciating the importance and fast development of power electronics, three special issues dedicated to this topic had been published in the *Bulletin of the Polish Academy of Sciences: Technical Sciences* until 2017:

- “Control in Power Electronics and Drives”, *Bull. Pol. Ac.: Tech.* 54 (3), 2006.
- “Power Electronics in Renewable Energy Systems”, *Bull. Pol. Ac.: Tech.* 57 (5), 2009.
- “Power Electronics for Smart Grids”, *Bull. Pol. Ac.: Tech.* 59 (4), 2011.

The newest Special Section is intended to focus on recent research and trends in application of multilevel converters. Multilevel converters have been extensively developed over the last two decades and show several important advantages of power electronic circuits, such as: operation at high voltages, harmonics reduction, higher efficiency, modularity, smaller size and lower cost. Also, thanks to increasing interest in renewable energy systems (RES) and SGs, the development of multilevel converters is considerably accelerated. The papers included in the presented special section are grouped into the main categories that follow.

1. Survey papers presenting the state of the art of cascaded multilevel converters [4] and converters for interfacing different types of energy storage [5]. The paper authored by an outstanding specialist from the Warsaw University of Technology, Poland, M. Malinowski [4] have a survey nature, covering different aspects of the technology and its applications. As shown, the cascaded multilevel converters can easily operate at medium and high voltage based

on the series connection of power modules using standard low-voltage components. It allows for low THD output voltages and input currents, reduction of passive components and redundancy of components. Thanks to these features, the cascaded multilevel converters have been recognized as attractive solutions for HVDC transmission, SST and photovoltaic (PV) systems.

The timely problem of how to interface different types of energy storages with power grid is addressed by an exceptionally experienced team of specialists: A. Domino, K. Zymmer and M. Parchomiuk from the Electrotechnical Institute (IEL), Warsaw, Poland [5]. They present an overview of converter topologies for energy storage, such as superconducting magnetic energy storage (SMES), supercapacitor energy storage (SES) and chemical batteries.

2. Modern predictive control methods developed for 5-level converter [6], 4-leg 3-level active filter [7], and 3-level grid-connected converter [8]. In power electronics, the model predictive control allows to change the control structure from classical series connected regulators (cascade structure) to one controller operating with on-line optimization. This is now possible, in spite of a high number of calculations required, thanks to very fast DSPs and FPGA processors. Therefore, many researches attempt to develop new algorithms optimizing several converter parameters in on-line fashion. How the current control in 5-level converter with boost capability can be implemented based on predictive model is presented by researchers from the Electrotechnical Institute (IEL), Warsaw, Poland, P. Wiatr and A. Kryński in [6]. This work presenting experimental results is a continuation of paper [16], in which a simulation study was described. The problem of calculation reduction in complicated control algorithm of the 4-leg 3-level flying capacitor converter (FCC) operating as shunt active power filter (SAPF) is discussed in the work by K. Rafał and K. Antoniewicz from Warsaw University of Technology, Poland [7]. The control algorithms of an AC-DC grid-connected converter have to provide not only a sinusoidal shape of grid current, but also stable operation during transient states in the grid, e.g. voltage dips or voltage unbalance.

This problem has been deeply discussed by a team from Białystok University of Technology P. Falkowski, K. Kulikowski, and R. Grodzki in [8], where three modern predictive control algorithms are presented and investigated under grid voltage distortions.

3. Space vector modulation (SVM) in multilevel converters [9] and in special application [10]. The fundamental problem: how to compensate for DC-link voltage unbalance in a 7-level cascaded H-bridge converter is considered in paper [9] by A. Lewicki and M. Morawiec from Gdansk University of Technology, Poland. The proposed SVM method allows to maintain the same balanced voltage level on all converter capacitors and generate the output voltage vector properly also in the case where the DC-link voltages are not balanced. The effect of SVM algorithm on current vector ripples, analyzed using the mathematical model of 3-level three-phase voltage inverter with symmetric active inductive load, has been discussed by V. Tomasov, A. Usoltsev, P. Zolov and P. Gribanov from ITMO University, St. Petersburg, Russia [10]. Some limitations on application of such inverters for precision drive control in optical telescopes were specified.

4. Special issue of high power multilevel converters [11–15]. The design and investigation results of switched capacitor voltage multipliers for application in high power systems is presented by the team of outstanding specialists from AGH University of Science and Technology, Krakow, Poland [11]. The considered family of multilevel converters includes classical topologies and also novel concepts. The application of thyristors as well as invention of novel concepts of multiplier topologies with appropriate control make it possible to achieve high efficiency, high voltage gain, as well as reliable and simple DC-DC converters for high power systems. The fundamental problem of how to increase the DC fault ride-through capability of a full-bridge modular multilevel converter (MMC) station while ensuring a stable controlled operation as a STATCOM during DC faults without the need for fault isolation is deeply discussed and well illustrated by the international team of excellent researchers E. Kontos, and P. Bauer from Delft University of Technology, The Netherlands with G. Tsolaridis and R. Teodorescu from Aalborg University, Denmark in [12]. Similarly, paper [13] presenting a comparative analysis between simulation results delivered for 2-level and 3-level 3kV traction drive system regarding generation of disturbing current harmonics, is written by an international team of authors: M. Steczek from Lodz University of Technology, Poland, A. Szeląg from Warsaw University of Technology, Poland, and D. Chatterjee from Jadavpur University, India. This problem is very important because every traction vehicle to be authorized for operation on railway lines must comply to the limits imposed on current harmonics magnitudes. In paper [14] by M. Morawiec and A. Lewicki from Gdansk University of

Technology, Poland, the control strategy for power electronic transformer (PET, also known as SST) is proposed. The analyzed structure uses two 7-level cascaded H-bridge (CHB) rectifiers. The electrical power is transferred between DC-links of CHB converters using dual-active-bridges (DABs) and low voltage high frequency transformers. The system allows to control the active and reactive power with low level of harmonic distortions. Finally, the last paper in this group, written by P. Błaszczuk, K. Koska and P. Klimczak from ABB Corporate Research Center, Krakow, Poland, presents energy balancing in modular multilevel converters (MMC). The analysis includes multi-converter systems, and the MMC control system is divided into hierarchical levels. It is important that experimental results, based on multi-converter test setup, are also added.

Acknowledgements. First of all, we would like to express our gratitude to all authors of papers included in this Special Section on Multilevel Converters, which presents results obtained by eleven research institutions. Also, we would like to thank all the reviewers for their efforts and valuable input, which contributed significantly to improving the quality of papers. Very special acknowledgments are addressed to Prof. Tadeusz Kaczorek, Editor-in-Chief, and all members of the Editorial Board for giving Guest Editors the opportunity to present this Special Section. Finally, we would like to thank Ms. Anna Jurkiewicz, Copy Editor, for her professional help and assistance.

REFERENCES

- [1] H. Abu-Rub, M. Malinowski, and K. Al-Haddad, *Power Electronics for Renewable Energy Systems, Transportation and Industrial Applications*, IEEE Press and J. Wiley & Sons Ltd., 2014.
- [2] N. Mohan, T.M. Undeland, and W.P. Robbins, *Power Electronics: Converters, Applications, and Design*, J. Wiley & Sons, Third Edition, 2003.
- [3] M.P. Kazmierkowski, R. Krishnan, and F. Blaabjerg, *Control in Power Electronics*, Academic Press, USA, 2002.
- [4] M. Malinowski, "Cascaded multilevel converters in recent research and applications", *Bull. Pol. Ac.: Tech.* 65 (5), 567–578 (2017).
- [5] A. Domino, K. Zymmer, and M. Parchomiuk, "Selected converter topologies for interfacing energy storages with power grid", *Bull. Pol. Ac.: Tech.* 65 (5), 579–588 (2017).
- [6] P. Wiatr and A. Kryński, "Model predictive control of multilevel cascaded converter with boosting capability – experimental results", *Bull. Pol. Ac.: Tech.* 65 (5), 589–600 (2017).
- [7] K. Rafał and K. Antoniewicz, "Model predictive current control method for four-leg three-level converter operating as shunt active power filter and grid connected inverter", *Bull. Pol. Ac.: Tech.* 65 (5), 601–608 (2017).
- [8] P. Falkowski, K. Kulikowski, and R. Grodzki, "Predictive and look-up table control methods of a three-level AC-DC converter under distorted grid voltage", *Bull. Pol. Ac.: Tech.* 65 (5), 609–618 (2017).
- [9] A. Lewicki and M. Morawiec, "Space-vector pulsewidth modulation for a seven-level cascaded H-bridge inverter with the control of DC-link voltages", *Bull. Pol. Ac.: Tech.* 65 (5), 619–628 (2017).

- [10] V. Tomasov, A. Usoltsev, P. Zolov, and P. Gribov, "The effect of space vector modulation algorithm on characteristics of three-phase voltage inverter for drivers of optical telescopes", *Bull. Pol. Ac.: Tech.* 65 (5), 629–638 (2017).
- [11] R. Stala, S. Piróg, A. Penczek, A. Kawa, Z. Waradzyn, A. Mondzik, and A. Skala, "A family of high power multilevel switched capacitor-based resonant DC-DC converters – operational parameters and novel concepts of topologies", *Bull. Pol. Ac.: Tech.* 65 (5), 639–652 (2017).
- [12] E. Kontos, G. Tsolaridis, R. Teodorescu, and P. Bauer, "Full-bridge MMC DC fault ride-through and STATCOM operation in multi-terminal HVDC grids", *Bull. Pol. Ac.: Tech.* 65 (5), 653–662 (2017).
- [13] M. Steczek, A. Szela, and D. Chatterjee, "Analysis of disturbing effect of 3 kV DC supplied traction vehicles equipped with two-level and three-level VSI on railway signalling track circuits", *Bull. Pol. Ac.: Tech.* 65 (5), 663–674 (2017).
- [14] M. Morawiec and A. Lewicki, "Power electronic transformer based on cascaded H-bridge converter", *Bull. Pol. Ac.: Tech.* 65 (5), 675–684 (2017).
- [15] P. Błaszczyk, K. Koska, and P. Klimczak, "Energy balancing in modular multilevel converter systems", *Bull. Pol. Ac.: Tech.* 65 (5), 685–694 (2017).
- [16] P. Wiatr and M.P. Kazmierkowski, "Model predictive control of multilevel cascaded converter with boosting capability – a simulation study", *Bull. Pol. Ac.: Tech.* 64 (3), 581–590 (2017).




e-mail: p.bauer@tudelft.nl

Pavol Bauer is currently a full Professor and head of DC Systems, Energy Conversion and Storage group of Delft University of Technology. He published over 80 journal and 300 conference papers in his field (with H factor: 21, Web of Science), he is author or co-author of 8 books, holds 4 international patents and organized several tutorials at international conferences. He has worked on many projects for industry concerning wind and wave energy, power electronic applications for power systems such as Smarttrafo, as well as HVDC systems and projects for smart cities such as PV charging of electric vehicles, PV and storage integration, and contactless charging. He is a former chairman of Benelux IEEE Joint IAS, PELS and PES chapter, Chairman of the Power Electronics and Motion Control (PEMC) Council, member of the Executive Committee of European Power Electronics Association (EPE) and also member of international steering committees of numerous conferences.



e-mail: mpk@isep.pw.edu.pl

Marian P. Kazmierkowski received the M.S., Ph.D., and D.Sc. degrees in electrical engineering from the Institute of Control and Industrial Electronics (ICIE), Warsaw University of Technology, Warsaw, Poland, in 1968, 1972, and 1981, respectively. He is currently a Full Professor with ICIE and a Consultant with the Electrotechnical Institute (IEL), Warsaw, Poland. Prof. Kazmierkowski was Vice-President of the IEEE Industrial Electronics Society (1999–2001) and Editor-in-Chief of the IEEE TRANSACTIONS ON INDUSTRIAL ELECTRONICS (2004–2006). In 2007 he was elected as a Corresponding Member and in 2016 as an Ordinary Member of the Polish Academy of Sciences. In 2010–2014, he served as the Dean of Division IV: Engineering Sciences, Polish Academy of Sciences. In 2017 he was recipient of the IEEE Medal in Power Engineering.



Ryszard Strzelecki was born in Bydgoszcz, Poland. He received the M.Sc. and Ph.D. degrees in electronic engineering from the Department of Industrial Electronics, National Technical University of Ukraine "Kyiv Polytechnic Institute," Kyiv, Ukraine, in 1981 and 1984, respectively, and the D.Sc. degree in electrical engineering from the Institute of Electrodynamics, the National Academy of Sciences of Ukraine, Kyiv, in 1991. He is currently Head of the Laboratory of Power Electronics and Automated Electric Drive, ITMO University, St. Petersburg, Russia, and Full Professor with the Gdynia Maritime University, Gdynia, Poland, and Electrotechnical Institute, Warsaw, Poland. His research activities are concentrated on the topology, control, and industry application of power electronic conditioners, particularly for power quality enhancement and power flow control on distributed electrical networks.