


Accepted Manuscript

State of the art and prospects of methods for determination of lipophilicity of chemical compounds

Dagmara Kempnińska, Tomasz Chmiel, Agata Kot-Wasik, Anna Mróz, Zofia Mazerska, Jacek Namieśnik



PII: S0165-9936(18)30066-9

DOI: <https://doi.org/10.1016/j.trac.2019.01.011>

Reference: TRAC 15387

To appear in: *Trends in Analytical Chemistry*

Received Date: 20 February 2018

Revised Date: 10 December 2018

Accepted Date: 21 January 2019

Please cite this article as: D. Kempnińska, T. Chmiel, A. Kot-Wasik, A. Mróz, Z. Mazerska, J. Namieśnik, State of the art and prospects of methods for determination of lipophilicity of chemical compounds, *Trends in Analytical Chemistry*, <https://doi.org/10.1016/j.trac.2019.01.011>.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

State of the art and prospects of methods for determination of lipophilicity of chemical compounds

Dagmara Kempieńska¹, Tomasz Chmiel^{1*}, Agata Kot-Wasik¹, Anna Mróz², Zofia Mazerska², Jacek Namieśnik¹

¹ Department of Analytical Chemistry, Faculty of Chemistry, Gdansk University of Technology, 11/12 G. Narutowicza St., 80-233 Gdańsk, Poland

² Department of Pharmaceutical Technology and Biochemistry, Faculty of Chemistry, Gdansk University of Technology, 11/12 G. Narutowicza St., 80-233 Gdańsk, Poland

* corresponding author (tomasz.chmiel@pg.edu.pl)

Abstract

Lipophilicity of the compounds is useful to (i) explain their distribution in biological systems, which is different in plant and in animal organisms, (ii) predict the possible pathways of pollutant transport in the environment, and (iii) support drug discovery process and select optimal composition in terms of bioactivity and bioavailability. The lipophilic properties can be determined by two main approaches, experimental, which apply instrumental techniques or computational, which is based on the complex algorithms. This review focuses primarily on various analytical methods that are used in the lipophilicity measurements. The classical methods and others based on chromatographic, electroanalytical and electroseparation approaches are compared and described in details. Modern solutions with chromatographic systems and their practical applications in the measurements of lipophilic and biomimetic properties of compounds have been included. However, there is an urgent need to standardize the high-throughput and reliable analytical procedure of the evaluation of lipophilic properties.

Abbreviations:

ACN, Acetonitrile; AGP, α_1 -Acid glycoprotein; CD, Conductivity detector; CE, Capillary electrophoresis; CHI, Chromatographic hydrophobicity index; CMC, Critical micelle concentration; CTAB, Cetyltrimethylammonium bromide; CV, Cyclic voltammetry; DDT, Dichlorodiphenyltrichloroethane; DMSO, Dimethyl sulfoxide; ECD, Electron capture detector; ED, Electrochemical detector; EDC, 1,2-Dichloroethane; EKC, Electrokinetic chromatography; ELSD, Evaporative light scattering detection; EOF, Electroosmotic flow; ESI-TOF-MS, Electrospray ionization time-of-flight mass spectrometry; FID, Flame ionization detector; FLD, Fluorescence detector; GC,

31 Gas chromatography; HSA, Human serum albumin; IAM, Immobilized artificial membrane; IPA,
32 Isopropyl alcohol; IP-HPLC, Ion-pair high performance liquid chromatography; LI, Lipophilicity Index;
33 IUPAC, International Union of Pure and Applied Chemistry; MeOH, Methanol; MEKC, Micellar
34 electrokinetic chromatography; MEEKC, Microemulsion electrokinetic chromatography; MOPS, 4-
35 Morpholinepropanesulfonic acid; MP, Mobile phase; MS, Mass spectrometry; NMR, Nuclear magnetic
36 resonance; NP, Normal phase; OD-PVA, Octadecyl-poly(vinyl alcohol); ODS, Octadecyl-bonded
37 silica; OECD, Organization for Economic Co-operation and Development; PBS, Phosphate buffer
38 saline; PDMS, Polydimethylsiloxane; PGDP, Propylene glycol dipelargonate; PBS, phosphate buffer
39 saline; PS, polystyrene; PS-DVB, Polystyrene-divinylbenzene; RID, Refractive index detector; RP-
40 HPLC, Reversed-phase high performance liquid chromatography; RP-TLC, Reversed-phase thin-
41 layer chromatography; RT, Retention time; RTILs, Room-temperature ionic liquids; SDS, Sodium
42 dodecyl sulfate; SFM, Shake-flask method; SP, Stationary phase; SPME, Solid phase
43 microextraction; SSM, slow stirring method TBAB, Tetrabutylammonium bromide; TEA, Triethylamine;
44 THF, Tetrahydrofuran; TMAC, Tetramethylammonium chloride; UV-Vis, ultraviolet-visible
45 spectrophotometry; VEKC, Vesicular electrokinetic chromatography.
46 D, Distribution coefficient; k, Retention factor (liquid chromatography); k', Retention factor
47 (electro-separation methods); K, Distribution constant; K_{oa} , n-octanol-air partition coefficient; K_{oc} ,
48 organic carbon-water partition coefficient; P (K_{ow}), n-octanol/water partition coefficient; pKa, acid
49 dissociation constant.

50

51 Keywords:

52 Lipophilicity; Shake-flask method; Potentiometric titration; High-performance liquid chromatography;
53 Thin-layer chromatography; Capillary electrophoresis; Electrokinetic chromatography; Cyclic
54 voltammetry

55 Contents**56 1. Introduction****57 2. Classical methods for lipophilicity determination****58 3. Separation and electroanalytical methods for lipophilicity determination****59 3.1. Chromatographic methods****60 3.1.1. Thin-layer chromatography based methods**

89 aqueous phase, distribution and partition coefficients are related through Eq. 2 and Eq. 3,
90 respectively:

$$91 \quad \log D_{\text{acids}} = \log P - \log(1 + 10^{\text{pH} - \text{pK}_a}) \quad (2)$$

$$92 \quad \log D_{\text{bases}} = \log P - \log(1 + 10^{\text{pK}_a - \text{pH}}) \quad (3)$$

93 where pK_a is acid dissociation constant. According to these equations (Eq. 2, 3) the solubility of an
94 ionizable compound increases exponentially with the difference between pH and pK_a [7].

95 The lipophilic properties of the compounds allow to characterize chemicals according to several
96 aspects. First, they help to explain distribution of the compounds and to predict their transport in
97 different biological systems considering the fact that the relations between lipophilic/hydrophilic
98 properties are different in plant and animal organism. The second aspect considers the prognosis of
99 the pollutant pathway in the environment. This knowledge allows to determine compound ability to be
100 transported in and between the environment compartments or the possible place of its accumulation
101 [3,8]. Partition coefficient K_{ow} is a useful index of the potential for bioaccumulation, bioconcentration
102 and biomagnification of environmental pollutants. It has been assumed that bioaccumulation does not
103 occur for substances with K_{ow} value lower than 2000 ($\log K_{\text{ow}} < 3.3$), whereas easy bioaccumulated
104 substances with tendency to biomagnification through food chain exhibit $\log K_{\text{ow}}$ higher than 5 [9],
105 which can be determined by some of the methods listed in Table 1. This coefficient is also related with
106 n-octanol-air partition coefficient (K_{oa}) that describes partitioning between atmosphere and terrestrial
107 environment or the organic carbon-water partition coefficient (K_{oc}) that is useful in the prediction of the
108 mobility of organic soil contaminants [10–13]. The lipophilic properties are also useful for chemicals in
109 respect to their optimal attribute for specific tasks in the industry [2,4].

110 The pathway of drugs and food components to reach their target site is complex since adsorption
111 depends on solubility and permeability. Both properties are influenced by the lipophilicity of the
112 compounds, however, in a different way. Moreover, the degree of ionization affects compound's
113 lipophilicity and it influences its solubility and permeability thus absorption too [5,14–17]. The
114 absorbed compounds undergo metabolic transformations, which can result in the changes of
115 physicochemical properties such as the molecule size or mass, charge and lipophilicity [18,19]. Due
116 to the complex nature of bioactive compounds in drugs and food as well as their different mechanism

117 of absorption and metabolism [7,20] the lipophilic characteristics performed on biomimetic stationary
118 phases (SPs) are useful tools in the assessment of biological effects of these components.
119 Consequently, the specific partition coefficients determined with the application of immobilized
120 artificial membrane (K_{IAM}), human serum albumin (K_{HSA}) and α_1 -acid glycoprotein (K_{AGP}), have been
121 proposed [21].

122 Therefore, the lipophilic characteristics of environmental pollutants, food-derived bioactive compounds
123 and drug ingredients can help to better understand their fate outside and inside the living organisms
124 and to build models for biological absorption and partition processes trying to predict *in vivo*
125 distribution of potential bioactive molecules (i.e. nutraceuticals and pharmaceuticals) [22,23].

126 Considering above, logP value of the solute allows to propose the fate of the chemical in the body as
127 it describes compound ability to reach its intended target. Moreover, the lipophilicity of the compounds
128 can be used as input parameters to design models for prediction of environmental transport of
129 pollutants between water phase and natural organic matter in soil and sediments including the
130 transport by biological membranes. In addition, the distribution between water and soil sediments
131 relates also to chemicals of food chain and those undergoing the ingestion [3,13,16].

132 In recent years, the studies of lipophilic properties of bioactive compounds, including pharmaceuticals
133 and natural products, as well as toxins, including environmental pollutants, have become a topic of
134 increasing interest. In fact, a literature search performed on the Web of Science and Scopus
135 databases revealed that the number of publications on lipophilicity and partition coefficient has
136 quadrupled or even increased fivefold (Fig. 1) in the past two decades (28084 or 71601 until 1997,
137 while between 1998-2018 around 153805 or 274422 scientific papers have been published according
138 to Web of Science and Scopus search engine, respectively).

139 This tendency has provided development of different approaches in lipophilicity determination (see
140 Table 1). We propose to divide them into classical methods and a set of methods based on different
141 backgrounds: chromatographic, electroseparation, potentiostatic or voltamperometric (Fig.2). The well
142 recognized classical methods are shake-flask technique or stir-flask technique, whereas a variety of
143 chromatographic methods (reversed-phase thin-layer chromatography (RP-TLC) and reversed-phase
144 high-performance liquid chromatography (RP-HPLC)) are today the most popular ones [24,25]. Main
145 advantages and limitations of the lipophilicity determination techniques are shown in Table 1 and will

146 be discussed in details further. The logP values can be also calculated using various computer
147 softwares or Internet available modules that applied different algorithms based on structural,
148 atomistic, topological, electrotopological, or other considerations on a drawn chemical structure [26].

ACCEPTED MANUSCRIPT

149 **Table 1.** Comparison of methods for determination of lipophilicity based on their usefulness, main advantages and limitations.

	SFM	SSM	Potentiometric titration	TLC	HPLC	CE	EKC methods	CV
Measurement	Direct	direct	direct	indirect	indirect	indirect	indirect	indirect
LogP range	Classic: $-3 < \log P < 4$ Miniaturized: $-2 < \log P < 6$ SPME-based: $0 < \log P < 5$	$\log P > 5$	$-1 < \log P < 8$	$4 < \log P$	$-3 < \log P < 8$	$0 < \log P < 5$	$-1 < \log P < 7$	$-8 < \log P < 1$
Sample amount required	Classic: 10-50 mg Miniaturized: 1-10 mg SPME-based: <2 mg	10-50 mg	2-50 mg	2-10 mg	<1 mg	<1 mg	1-2 mg	1-10 mg
Partition solvent	n-octanol, aqueous buffer systems	water, n-octanol	n-octanol, KCl	water and organic solvent (e.g. MeOH, ACN, THF, dioxane)	aqueous buffer, ACN or MeOH	buffers	buffers, surfactants	1,2-dichloroethane or nitrobenzene, buffers
Consumption of organic solvent	Classic: high Miniaturized: low SPME-based: solventless	high	low	very low	Isocratic: low to medium Gradient: very low	low	low	medium
pH range	$0 < \text{pH} < 14$	$0 < \text{pH} < 14$	$1.8 < \text{pH} < 12.2$	$2 < \text{pH} < 11$	Isocratic: $1.5 < \text{pH} < 10.5$ (13*) Gradient: $1 < \text{pH} < 12$ (13*)	$2 < \text{pH} < 12$	$2 < \text{pH} < 12$	$0 < \text{pH} < 14$
Apparatus required	Classic: basic glassware and labware, UV-Vis spectrophotometer or LC system (LC-UV, LC-MS) or NMR detection Miniaturized: multi-well plates, liquid handling robot, shaker and centrifuge for plates, highly sensitive quantification system	basic glassware and labware, GC or LC system with appropriate detection (e.g. FID, ECD, MS, UV)	potentiometric titrator with a set of electrodes	manual or fully automated TLC system with detection unit (UV, FLD); fast, reproducible, high-throughput, but more expensive	LC system with various detection (UV, FLD, MS, MS/MS)	CE system with CD, ED, FLD, UV or MS detection	CE system with CD, ED, FLD, UV or MS detection	typical apparatus for electrochemical measurements



	(LC-UV/MS, LC-MS/MS, NMR); high-throughout, but more expensive approach			approach				
	SPME-based: SPME device, GC or LC system with appropriate detection (e.g. FID, ECD, MS, UV)							
Time consumption	Classic: ~1 day Miniaturized: 10-30 min; up to 200 compounds/day SPME-based: up to 2 h (depending on type of SPME fiber used)	2-4 days	up to 30 min; determination of lipophilicity profile of one compound	30-60 min; simultaneous analysis of several to several dozen compounds	Isocratic: 30-120 min (depends on the dimension of the column used); several compounds in single run Gradient: 5-20 min; up to tens of compounds per run	up to 60 min; simultaneous analysis of several to several dozen compounds	15-30 min; 20-30 compounds per run (2 h) in multi-well plate format	up to 30 min; single measurements
Lipophilicity index determined	Classic, miniaturized: logP SPME-based: logK	logP	logD, logP ^N , logP ^I	R _M , R _{M0}	Isocratic: logk, logk _w , S, CHI, logP Gradient: CHI, k _g , logP, logD	logP	logk', logP	logP ^{0,i}
Application	Neutral and ionizable compounds (only in their neutral form), limited to highly hydrophobic and sparingly soluble compounds	Highly hydrophobic compounds in neutral form	Ionizable compounds with acid-base properties	Neutral compounds, ionizable compounds only in their unionized form (appropriate mobile phase pH and composition is required)	Neutral compounds, ionizable compounds only in their unionized form (appropriate mobile phase pH and composition is required)	Cations and anions of inorganic and organic salts	Neutral compounds	Ionizable compounds

* pH limit for polymer-based stationary phases of HPLC columns; CD – conductivity detector; ECD – electron capture detector; ED – electrochemical detector; FID – flame ionization detector; FLD – fluorescence detector; SPME – solid-phase microextraction; CHI – chromatographic hydrophobicity index; D – distribution coefficient; k – retention factor in LC methods; k' – retention factor in EKC methods; k_g – apparent gradient capacity factor; k_w – retention factor extrapolated to zero organic phase concentration; K – distribution constant; P – n-octanol/water partition coefficient; P^I – partition coefficient of ionized forms; P^N – partition coefficient of neutral forms; R_M – retardation parameter; S – slope of the linear relationship between the organic solvent concentration (φ) and the logk



150 2. Classical methods for lipophilicity determination

151 The oldest and the most known method of lipophilicity measurement, shake-flask method (SFM), is
152 based on liquid-liquid extraction using n-octanol/water system [24]. The analyzed substance is
153 dissolved in two flasks, the first one filled with aqueous buffer solution and the second one containing
154 an organic solvent (n-octanol). Both solutions should be saturated before the compound introduction,
155 buffer with n-octanol, and n-octanol with water. These solutions are introduced to the laboratory
156 separator and then shaken to achieve equilibration of the solute between the aqueous and organic
157 phases as shown in Fig.3a [27]. After the equilibrium is reached, UV-Vis spectrophotometry or other
158 appropriate analytical method is employed to determine the concentration of the compound dissolved
159 in each phase [23].

160 Due to the simplicity and evident correlation with partitioning phenomenon, SFM is recommended as
161 a benchmark procedure for the other methods. However, reliable measurement of lipophilicity by this
162 method is only achievable in the logP range from -3 to 4 [27–29]. Furthermore, the procedure is
163 tedious and time-consuming and requires relatively large amount of pure solutes. In addition, there is
164 a possibility of formation of stable emulsions after the shaking step [28,30–33]. Emulsion in n-
165 octanol/water system can be a serious problem, particularly in the case of the hydrophobic
166 compounds. The logK_{ow} depends on relative solubility of the compound in water and organic solvents
167 and it has to be corrected for ionization. Moreover, due to amphiphilic properties, some compounds
168 may behave as detergents [23,30,34]. Modifications of this classical method (Fig.3) enable to handle
169 with some of limitations described above. In case of model of biological partition, different solutions
170 are used to determine the partition coefficient. Aside from n-octanol/water set, which is characterized
171 by the properties of hydroxyl group connected with function of hydrogen-bond donor and acceptor,
172 some other solvents that allow to imitate different physiological cell barriers have been proposed.
173 These systems include chloroform and water (a set with largely proton donors) or alkane (e.g.
174 cyclohexane or dodecane) and water (a set without hydrogen acceptors and donors) or propylene
175 glycol dipelargonate (PGDP) and water (a set with largely proton acceptors as in phospholipid
176 membranes). PGDP, chloroform, n-octanol and cyclohexane are known as solvents that encoding
177 important hydrogen bonding properties. Due to hydrogen bonding effects, the values of partition
178 coefficient measured in these four solvents are different but their forces account for membrane
179 partitioning. Lipophilicity parameters measured experimentally for these solvent systems are partially

180 dependent on the reference system and vary from classical n-octanol/water partition coefficient. The
181 n-octanol/water model does not reflect the drug partitioning in biological structures anymore, thus
182 these critical quartet (chloroform, cyclohexane, n-octanol and PGDP) has been proposed to be used
183 instead of one organic solvent [35,36].

184 Miniaturization of SFM has led to the development of the high-throughput methods for screening of
185 new targets with pharmacological effects. In traditional procedure even hundreds milliliters of each
186 phase was used during the extraction. Nowadays, the volume of organic and aqueous solvents has
187 trimmed down to less than 1 mL and the 96-well plate format of SFM has been presented [37]. The
188 miniaturized SFM may be coupled with sensitive detection technique, such as mass spectrometry
189 (MS). The LC-UV/MS systems have been successfully applied for the final determination step and the
190 obtained results were in good correlation with literature values. The biggest advantages of the
191 miniaturized method are rapidity, great flexibility, the use of small amount of solutes, the extended
192 range of measured logP (from -2 to 6) and the potential to be fully automated. However, the
193 miniaturization does not exclude the emulsion problem, especially for hydrophobic compounds
194 [23,37–39].

195 In case of poorly water soluble substances, the lipophilicity may be determined by automated
196 continuous sampling method, called filter probe method. This method is simple, partially automated
197 and time-saving. Furthermore, computer program monitoring showed that filter probe method ensured
198 greater accuracy and reproducibility [40]. However, during the analysis of the partition coefficient of
199 highly hydrophobic compound, the concentration of this compound in organic phase is much higher
200 than that in aqueous phase. In such case, contamination of aqueous phase by n-octanol layer is
201 usually occurring during sampling. To solve this problem, the water-plug aspiration/injection method
202 has been developed. In this method, the sample is taken by a small syringe with needle filled with a
203 few microliters of water as a plug. This is expected to prevent contamination while the needle is
204 passing through the n-octanol layer to reach sample in the aqueous layer, because the water plug
205 stops the entrance of the n-octanol into the needle [38].

206 Another modification of classical methods applied for the determination of logP is the procedure
207 based on nuclear magnetic resonance spectroscopy (NMR). The extraction step takes places in NMR
208 tubes, content of which is vigorously mixed for 20 minutes. The concentration of analyte in water

209 phase is measured twice: before addition of the n-octanol and after the extraction. Then, P value is
 210 calculated from the following equation (Eq. 4):

$$211 \quad P = (I_w - I_{w0})/I_w \quad (4)$$

212 where I_w and I_{w0} are the intensity of the signal of analyte in pure water and in water with n-octanol
 213 added, respectively. This method was proposed by Cumming and Rücker and so far it has been used
 214 to determine the partition coefficient of some common solvents, such as acetone and tetrahydrofuran
 215 (THF) [41]. Moreover, it is well-suited for fast and easy measurement of n-octanol-water partition
 216 coefficient of the compounds with sufficient water solubility and logP in the range from -1 to 1.

217 Another variation of the classical methods is the solid phase microextraction (SPME) developed by
 218 Pawliszyn [42]. During the solventless extraction, the sample partitions between aqueous phase
 219 (blood, urine or environmental water) and a fused silica fiber coated with a polymer. In SPME, the
 220 equilibrium is established as the partition of analytes between the stationary and aqueous phase, and
 221 it depends on distribution coefficients (D), the temperature of the sample, stirring rate, the ionic
 222 strength of the solvent and the thickness of the fiber coating [43–45]. The amount of analyte adsorbed
 223 by the fiber (N) at the equilibrium is defined by the following equation (Eq. 5):

$$224 \quad N = K \cdot V_s \cdot C_0 \quad (5)$$

225 where V_s is the volume of the SP, C_0 is the initial concentration of analyte in aqueous phase, and K is
 226 the distribution constant of analyte partitioning between the aqueous and stationary phase. However,
 227 when the value of distribution constant is high and the volume of sample is small, there is a possibility
 228 that analytes are mainly presented on the SP. In that case, the Eq. 6. should be used. According to
 229 this equation, the distribution coefficient is defined as:

$$230 \quad K = (N \cdot V_{aq}) / (V_s \cdot (V_{aq} \cdot C_0 - N)) \quad (6)$$

231 where V_{aq} is the volume of aqueous phase [46,47].

232 In 1996 Dean et al. proposed the use of the fused-silica fiber coated with polyacrylate for
 233 determination of the K of phenols. They confirmed that K values determined by SPME method can be
 234 correlated with logP values. Their results indicated that SPME was an appropriate method for
 235 estimating logP. Currently, the non-polar fiber coatings (i.e. polydimethylsiloxane (PDMS)) are
 236 commonly used in this technique. Studies have shown that distribution coefficients obtained by SPME
 237 with PDMS coating also correlate well with logK_{ow} values [47,48]. SPME coupled with gas
 238 chromatography, and less often with LC, and MS detection enables the determination of minimal

239 quantities of highly non-polar compounds in aqueous phase and minimizes the loss of volatile
240 compounds [49].

241 Slow stirring method (SSM) follows the same principle as SFM. However, the emulsion formation is
242 limited. Although this method allows to determine the logP of neutral compounds, it is time-
243 consuming, rather expensive and requires a large amount of sample [50–52].

244 **3. Separation and electroanalytical methods for lipophilicity determination**

245 Currently, classical methods of lipophilicity determination are almost totally replaced by indirect
246 methods that include chromatographic, electrochemical and electroseparation methods. In contrast to
247 time-consuming equilibration, chromatography and other techniques provide measurement of
248 extended range of lipophilicity during rapid analysis, in which the sample impurities usually do not
249 affect the measurements [24,53].

250 **3.1. Chromatographic methods**

251 Chromatographic methods have been applied for the lipophilicity determination since 1970s [54,55].
252 Due to their many advantages and relatively few limitations, nowadays they are the most popular
253 experimental indirect methods for estimating logP values.

254 **3.1.1. Thin-layer chromatography based methods**

255 TLC is a chromatographic technique used for separation of non-volatile mixtures. The first application
256 of TLC was the determination of impurities in pharmaceutical preparations and since 1938 this
257 technique has been applied in diverse fields of chemistry. The adaptability of TLC may offer lots of
258 new possibilities to evaluate lipophilic character [24]. In this case, different reversed-phase modes
259 (see Table 2) are commonly used where the stationary phase is a foil coated with thin layer of silica or
260 aluminum derivatives, both modified with hydrophobic ligand bounded covalently or by absorption,
261 and the mixture of water and water-soluble organic solvent works as the mobile phase (MP) [36]. The
262 retention of analytes can vary during changing the content of organic solvent in the MP and the
263 activity of SP is based on the contribution of many specific parameters influencing the
264 chromatographic behavior. The most important ones are the chemical structures of the sorbents, the
265 surface area, the density of the free active centers per unit of sorbent surface area and the energy of
266 intermolecular interactions between a molecule and a type of sorbent active centers. These

267 parameters affect the data obtained for measured lipophilicity of molecules, so the standardization of
268 the TLC procedure in relation with biological impact is needed [24,56].

269 The most popular chromatographic lipophilicity descriptor is the retardation parameter (R_M) defined by
270 Bate-Smith and Westall through the following formula (Eq. 7) [57]:

$$271 \quad R_M = \log((1/R_f) - 1) \quad (7)$$

272 where the R_f is the retention factor, which is calculated as the ratio of the migration distances of solute
273 and the solvent front. The R_M value depends linearly on the concentration of organic modifier in MP
274 and this relationship is described by a TLC adapted Soczewiński-Wachtmeister equation [58,59] (Eq.
275 8):

$$276 \quad R_M = -S \cdot \varphi + R_{Mw} \quad (8)$$

277 The value of R_{Mw} is extrapolated to pure water as a MP. The regression slope (S) is directly linked to
278 specific surface area of SP and is considered also as an alternative lipophilicity descriptor. The last
279 factor, φ , represents the volume of organic solvent in the MP [24,58,59].

280 The RP-TLC is easy to perform and rapid. It requires small amount of the samples and allows the
281 analysis of several compounds simultaneously. Moreover, there is no need to test pure compounds or
282 to perform the problematic quantitative analysis. This technique is especially suitable for the
283 investigation of compounds with low water solubility ($\log P > 4$). Furthermore, the use of TLC plates
284 coated with RP material allows to overcome some of the disadvantages associated with SFM,
285 because the reversed-phase mode simulates the process of n-octanol-water partitioning [23,25].

286 Recently, new approaches in the lipophilicity determination using TLC have been reported [60–62].
287 Janicka et al. have used micellar TLC and over-pressured-layer chromatography (OPLC) [60,63],
288 where surfactants (anionic sodium dodecyl sulfate (SDS), cationic cetyltrimethylammonium bromide
289 (CTAB) and non-ionic Brij-35) are used as the modifiers of MP. Due to amphiphilic character of
290 micelles formed, both non-polar and polar interactions between them and solutes take place during
291 the analysis. As a consequence, these systems are supposed to be more similar to biomembranes
292 than in classical TLC [64]. Another method applied for the lipophilicity evaluation is normal-phase TLC
293 (NP-TLC), where MP contains two organic solvents, polar (e.g. acetone, ethanol, ethyl acetate) and
294 non-polar (e.g. benzene, cyclohexane, carbon tetrachloride, toluene). An excellent review of these
295 TLC approaches for lipophilicity studies has been published lately [59].

296 **3.1.2. Liquid chromatography based methods**

297 The use of RP-HPLC as indirect method for the determination of lipophilic properties has been the
298 subject of several reviews [6,23,65–68]. Nowadays it has become one of the most commonly used
299 procedures in the lipophilicity studies recommended by Organization for Economic Co-operation and
300 Development (OECD). In general, this method is based on dynamic partitioning of a compound
301 between two immiscible phases, solid and liquid (SP of the column and MP) (Fig. 4), which is
302 consistent with the IUPAC definition of partition coefficient [69]. Based on the solvophobic theory the
303 interaction between the solute and the SP is considered as a reversible association of the solute
304 molecules with the SP moiety. The distribution of the compound between the SP and MP is directly
305 related to the chromatographic retention time (RT, t_R). The solute retention factor (k) is proportional to
306 the ratio of the average number of analyte molecules in the SP (n_s) to the average number of
307 molecules in the MP (n_m) during the chromatographic elution (Fig. 4). This lipophilicity index (LI) is
308 usually expressed using a logarithmic scale and can be related to the distribution constant (K) of the
309 compound between the MP and SP, as shown in Figure 4. Therefore, the retention of dissolved
310 compound is governed by this equilibrium constant [70].

311 Both equations shown in Figure 3 provide the theoretical basis for the partition data obtained from
312 retention of the compound in the selected chromatographic system. In contrast to the determination of
313 compound concentration required within the classical methods, only RT measurements are necessary
314 to determine the LIs by RP-HPLC procedures and thus it is the main indicator of a real partition
315 process. This chromatographic separation-based approach also provides other practical advantages:
316 speed up the experimental work, good reproducibility, process automation, broad dynamic range, on-
317 line detection (mainly UV-Vis or refractive index detector (RID)), small amount of sample required,
318 independence of measurements from low compound solubility as well as impurities or degradation
319 products. However, some limitations of the RP-HPLC method have also been noted, including (i)
320 insufficient modeling of the n-octanol-water system for structurally diverse compounds, (ii) pore size
321 effects for sorbents filling chromatographic column have no counterpart in the n-octanol-water
322 partition system, (iii) possible interactions with the surface of the SP that not occur in the n-octanol-
323 water system, (iv) time-consuming isocratic measurements in some cases, (v) limited pH working
324 range for most of the SPs (2.0-7.5). In order to overcome these drawbacks, some solutions have
325 been recently introduced, just to mention novel types of columns [21,71,72] that are designed to

326 mimic the n-octanol-water system or biological membranes and let to operate over a wide pH range
327 (1.0-12.0). Moreover, application of short columns with smaller inner diameter results in acceleration
328 of experiments and reduction of costs, especially reduced consumption of organic solvents.
329 Separations using micellar MPs, and gradient elution procedures have been proposed lately
330 [60,70,73,74].

331 3.1.2.1. Chromatographic partition systems for measuring lipophilic properties

332 One of the most important aspects in the lipophilicity assessment by HPLC is to develop a
333 chromatographic system that mimics the standard n-octanol-water partition system as closely as
334 possible. Therefore, various SPs as well as MP modifying agents have been introduced and tested for
335 this purpose. Improved or newly-developed SPs for the lipophilicity studies were summarized by
336 Kaliszan [75] and Giaginis et al. [76] and they include mainly silica-based, polymer-based and
337 biomimetic phases as shown in Table 2. Octadecyl-bonded silica (ODS) and other alkyl groups
338 bonded to silica core are one of the most commonly used SPs for HPLC-based lipophilicity
339 measurements. However, the possibility of polar moieties interactions, including hydrogen bonding or
340 electrostatic attraction, with the remaining free-silanol groups on the silica surface may affect the
341 partitioning mechanism of RP-HPLC and thus results in increases in RTs and peaks asymmetry
342 [67,75]. Therefore, the studies of lipophilic character of ionizable basic compounds on silica-based
343 columns can be difficult and give overestimated results [77,78].

344 Some improvements of silica-based SPs have been recently proposed. End-capping of the free-
345 silanol sites by short alkyl groups (i.e. trimethylsilyl group (TMS)) is usually performed in order to
346 provide higher degree of silanization [79] and thus make the column packaging material more suitable
347 for analysis of strong hydrogen-bonding and ionized compounds [80]. Another solution for reducing
348 effect of residual silanols is embedding or end-capping polar groups (i.e. amide, carbamate, ether,
349 sulfonamide or ammonium) in the alkyl chains [72]. Due to accurate mimicking of biopartitioning and
350 good correlation with K_{ow} , alkylamide-silica HPLC columns are one of the most frequently applied
351 phases of this type [71,81]. The possibility of use of MP with a high water content or even pure water
352 without the risk of hydrophobicity collapse of these type of SPs is an additional advantage. However,
353 the polar moieties incorporated into the silica backbone may interact with some analytes, i.e.
354 polyphenols and thus addition of masking agents is also required [67,82]. Octanol-coated SPs were



355 successfully applied for the estimation of logP of neutral or basic compounds [83,84]. On the other
356 hand, the problems associated with long-term stability of these columns may occur [6].

357 In order to overcome pH limitation of ODS columns and to make the lipophilicity assessment of basic
358 analytes in their neutral form possible, new generation of SPs have been developed. They include:
359 grafted polymer-silica hybrid columns [74,85,86], columns with hybrid organic-inorganic silica in which
360 hydroxyl groups are replaced by methyl ones, and columns based on the bidentate technology that
361 include a propylene bridge [71,72]. These types of column are protected from silanol interactions and
362 have an extended pH range capability up to 12 [82,86].

363 More recently, the polymer-based SPs, including octadecyl-poly(vinyl alcohol) (OD-PVA), and
364 polystyrene-divinylbenzene (PS-DVB) based columns, have also been successfully applied for the
365 lipophilicity measurements [87–90]. In contrast to silica-based SPs, the polymer-based resins are
366 rigid, macroporous, cross-linked polymers completely free of silanol groups and other polar sites, and
367 hence irreversible binding of polar compounds is eliminated [77]. Furthermore, these columns are
368 chemically inert in most organic solvents and stable over a wide pH range (1-13). However, their
369 retention mechanism is governed by a different balance of structural properties (mainly
370 dipolarity/polarizability parameter) as determined by linear solvation/free-energy relationships and
371 thus obtained results may correlate better to alkane-water than to n-octanol-water partitions, which
372 mimics the blood-brain partitioning more reliably [88,90]. Further evaluation of retention behavior on
373 polymer-based SPs is needed for better use in the lipophilicity studies.

374 As an alternative choice for a more accurate description of compound distribution between various
375 compartments *in vivo*, the SPs that could directly mimic biologically important elements and provide
376 biomimetic characteristic are increasingly used in recent years. These biomimetic SPs include IAMs,
377 liposomes and plasma proteins (i.e. HSA, AGP). The theoretical and practical aspects of using
378 biomimetic columns and their detailed characterization have been the subject of several reviews
379 [21,68,76,91–94]. The retention factors of compounds obtained using protein-based SPs can be
380 easily converted to binding parameters such as $\%HSA = 100 \times k / (k + 1)$. These columns provide
381 potential to simulate plasma protein binding, as retention mechanism incorporates other interactions
382 than in n-octanol-water partitioning, especially those of electrostatic nature. It should be noted that
383 since protein binding occurs naturally only at physiological conditions, there is no need to use MPs

384 with different pHs. Verification of protein SPs stability is also essential and can be easily ensured by
385 HPLC analysis of racemic mixture of warfarin that should revealed the separation of enantiomers
386 [21,68].

387 IAM columns introduced and patented by Pidgeon et al. [95] to model the lipid bilayers of the cells are
388 prepared by covalent binding of phospholipids monolayers (i.e. phosphatidylcholine) to amine-
389 modified silica support. IAM columns are highly stable with little phospholipid loss during analyses or
390 storage [96] and commercially available, including the single chain and double chain SPs, which differ
391 in the end-capping of free propylamine residues [97]. It is reported that double chain IAM phases
392 better simulates the structure of natural phospholipids and hence the resulting lipophilicity indices
393 correlate better with permeability data [98,99]. The amphiphilic character of phospholipid functional
394 groups play an important role in IAM retention especially if charged molecules are analyzed. Thus,
395 electrostatic interactions also affect the retention mechanism, which is mainly governed by
396 hydrophobic/solvophobic interactions [81,97]. It should be emphasized that pure water can be used
397 as a MP in IAM chromatography, which allows fast and direct determination of $\log k$ value extrapolated
398 to zero organic phase concentration referred as $\log k_w$. The addition of acetonitrile as organic modifier
399 is recommended, when compounds with high affinity for the IAM SP are analyzed and then $\log k_w$
400 values require extrapolation. A novel SPs that may simulate cell membrane partitioning in the similar
401 way as the IAM phases were introduced. They are *N,O*-dialkylphosphoramidate-based materials
402 having in their structure amine groups, phosphate groups and hydrophobic long alkyl chains [100].
403 Summarizing, the future trends in column development for the lipophilicity studies could be
404 immobilization of other important proteins, enzymes or membrane lipids on the SP or introduction of
405 similar functional groups to the silica surface and measure compound's interactions with them.

406 The mixtures of water and organic modifiers with some additives are commonly applied as MPs of
407 chromatographic partitioning systems for the lipophilicity measurements. To speed up RP-HPLC
408 analyses, especially of highly lipophilic compounds, methanol and acetonitrile are the most widely
409 used modifiers. Methanol appears to be the most suitable organic solvent for the lipophilicity studies
410 because it does not disturb the hydrogen-bonding network of water. On the other hand, acetonitrile,
411 which generates the most asymmetrical peaks for basic analytes, proves to better simulate the
412 'organic phase' [67,76]. The correlations between chromatographic hydrophobicity index (CHI, ϕ_0) and
413 $\log P$ values reported by Valko et al. using fast gradient RP-HPLC procedures showed that acetonitrile

414 serves as a better organic modifier than methanol for both ODS and IAM columns [70,101]. According
415 to the solvation equation, this results from the significant difference between the CHI_{MeOH} lipophilicity
416 scale and the logP scale in terms of H-bond acidity, H-bond basicity, size and dipolarity/polarizability.
417 In order to match the CHI_{ACN} scale with logP scale only H-bond acidity term should be considered
418 thus acetonitrile was suggested as the preferred organic modifier by Valko et al. [70]. THF and
419 isopropyl alcohol (IPA) are also used in some lipophilicity assays [73,102]. Due to the dissociation of
420 most analytes in aqueous MPs, some chemical additives are required. These MP additives have been
421 extensively discussed in many reviews [21,67,76,81,82] and therefore, only some important will be
422 highlighted here. They can be divided into two main groups: ion suppressors and masking agents. In
423 order to suppress dissociation of ionizable analytes and keep them in a neutral form different buffers
424 have been applied, including morpholinepropanesulfonic acid, phosphate buffer and phosphate-
425 buffered saline [82,84]. Ammonium acetate buffers are also used because they exhibit good
426 compatibility with mass spectrometry. Acetic or perchloric acid and ammonia or triethylamine (TEA)
427 were employed as ion suppressors in the lipophilicity assessment of weak acidic and weakly basic
428 compounds, respectively [103,104]. Masking agents including hydrophobic amines (i.e. TEA, *n*-
429 decylamine, *N,N*-dimethyloctylamine) and room-temperature ionic liquids (RTILs) are often used as
430 MP additives to reduce or even to suppress silanophilic interactions. A small addition of amines (0.15-
431 0.20%) is considered as the most suitable masking agents in combination with methanol as organic
432 modifier [82,84]. Unlike amines, RTILs have no effect on the pH of MP. However, the use of RTILs
433 complicates MS detection and may add noise or a background signal to UV detection [105,106]. In
434 recent years, the addition of small amount of *n*-octanol to the methanolic MP has improved the HPLC
435 determination of LIs. Almost 1:1 correlation between $\log k_w$ and logP or logD was obtained with *n*-
436 octanol-modified MP [86,107].



437 **Table 2. Chromatographic partition systems used in lipophilicity studies and their applications.**

Type of stationary phase	Mobile phase composition	Other important conditions	Type of analytes/samples	Measured LI	Ref.
THIN-LAYER CHROMATOGRAPHY SYSTEMS					
Silica gel TLC plate modified with: (1) cyanopropyl groups (CN), (2) octadecyl carbon chain (C ₁₈), both with F ₂₅₄ fluorescence indicator	(1) (a) Aqueous phase: CTAB Organic phase: ACN (b) Aqueous phase: SDS Organic phase: ACN (2) Aqueous phase: H ₂ O Organic phase: MeOH	Saturation: 20 min Visualization: mixture of MeOH and sulfuric acid Detection: UV	25 Aromatic compounds (e.g. ethylbenzene, eugenol, fenitroton, nabumeton, phenol, vanillin)	R _M , R _{Mw}	[62]
Silica gel TLC plate modified with: (1) cyanopropyl groups (CN), (2) octadecyl carbon chain (C ₁₈), (3) diol groups (DIOL), (4) octyl carbon chain (C ₈), (5) dimethyl groups (C ₂), all with F ₂₅₄ fluorescence indicator	(a) Aqueous phase: H ₂ O Organic phase: MeOH (b) Aqueous phase: H ₂ O Organic phase: dioxane	Saturation: 20 min Detection: densitometric scanning	Naproxen	R _{Mw}	[108]
Silica gel TLC plate modified with: (1) cyanopropyl groups (CN), (2) octadecyl carbon chain (C ₁₈), (3) diol groups (DIOL), (4) octyl carbon chain (C ₈), (5) dimethyl groups (C ₂), all with F ₂₅₄ fluorescence indicator	Aqueous phase: H ₂ O Organic phase: ACN or MeOH	Saturation: 20 min Detection: UV	8 Cephalosporins	R _{Mw} , R _M , PC1/R _M	[109]
Silica gel TLC plate modified with octadecyl carbon chain (C ₁₈) / F ₂₅₄ fluorescence indicator	Aqueous phase: H ₂ O Organic phase: ACN or MeOH or acetone	Saturation: 20 min Detection: UV	6 Statin drugs	R _{Mw} , C ₀	[110]
Silica gel TLC plate modified with: (1) cyanopropyl groups (CN), (2) octadecyl carbon chain (C ₁₈), (3) octyl carbon chain (C ₈), (4) amino groups (NH ₂), all with F ₂₅₄ fluorescence indicator	Aqueous phase: H ₂ O Organic phase: CAN	Saturation: 10 min Visualization: ethanolic solution of bromocresol green treated with NaOH Detection: UV	4 Artificial and 13 natural sweeteners	R _{Mw} , R _M	[24]



Silica gel TLC plate modified with: (1) cyanopropyl groups (CN), (2) octadecyl carbon chain (C ₁₈), (3) diol groups (DIOL), (4) octyl carbon chain (C ₈), (5) dimethyl groups (C ₂), all with F ₂₅₄ fluorescence indicator	Aqueous phase: phosphate buffer Organic phase: MeOH	Visualization: fluorescamine/ 2,2-diphenyl-1-picrylhydrazyl Detection: UV	3 Amine neurotransmitters and 18 derivatives	R _M , R _{Mw} , PC1/R _M	[111]
Silica gel TLC plate modified with: (1) octadecyl carbon chain (C ₁₈), (2) cyanopropyl groups (CN), both with F ₂₅₄ fluorescence indicator	(1) Aqueous phase: H ₂ O Organic phase: acetone, dioxane or MeOH (2) Aqueous phase: SDS Organic phase: THF	Saturation: 15 min Detection: UV	1,2,4-Triazoles (21 compounds)	R _{Mw}	[60]
Silica gel TLC plate modified with octadecyl carbon chain (C ₁₈) / F ₂₅₄ fluorescence indicator	Aqueous phase: H ₂ O Organic phase: acetone or ACN or MeOH or THF or IPA	Detection: UV	15 Fluoroquinolones	R _{Mw}	[112]
Silica gel TLC plate modified with: (1) octadecyl carbon chain (C ₁₈), (2) cyanopropyl groups (CN), both with F ₂₅₄ fluorescence indicator	Aqueous phase: H ₂ O Organic phase: MeOH	Saturation: 15 min Visualization: manganese chloride in sulfuric acid Detection: UV	Bile acids and their derivatives (27 compounds)	R _{Mw} , PC1/R _M	[113]
Silica gel TLC plate modified with cyanopropyl groups (CN) / F ₂₅₄ fluorescence indicator	(1) Aqueous phase: Brij (35) Organic phase: ACN (2) Aqueous phase: CTAB Organic phase: ACN (3) Aqueous phase: SDS Organic phase: acetone or dioxane or THF	Drying of plates: iodine vapor	13 Fatty acids and 4 polyphenols	P _{SW} , K _{ma}	[61]
Silica gel TLC plate modified with octadecyl carbon chain (C ₁₈) / F ₂₅₄ fluorescence indicator	Aqueous phase: H ₂ O Organic phase: acetone or DMSO	Saturation: 15 min Detection: UV	4-Amino-7-chloroquinoline based compounds (18 compounds)	R _{Mw} , R _M	[114]
HIGH-PERFORMANCE LIQUID CHROMATOGRAPHY SYSTEMS					
SILICA-BASED COLUMNS					
Kromasil C18 (250 mm × 4.6 mm, 5 μm particle size); Akzo Nobel / Eka Chemicals Inc.	Aqueous phase: H ₂ O (10%) Organic phase: MeOH (90%)	HPLC mode: isocratic Detection: RID	Non-ionic surfactants (alcohol ethoxylates) including highly hydrophobic substances (logP > 6)	logk, logP	[115]
Spherex C18 (250 mm × 4.6 mm, 5 μm particle size); Phenomenex Inc.	Aqueous phase: H ₂ O (35-90%) Organic phase: MeOH (10-65%) Masking agent: 10 mM TMAC	HPLC mode: isocratic Detection: UV (220 nm) Dead time marker: KBr	22 Penicillin drugs	logk, logk _w	[116]
C18 column (250 mm × 4 mm, 5 μm)	Aqueous phase: H ₂ O (15%)	HPLC mode: isocratic	16 Polycyclic aromatic hydrocarbons	logk, logP	[117]



particle size)	Organic phase: MeOH (85%)	Detection: UV (254 nm)	(3.3 < logP < 6.3)		
Altima C18 (150 mm × 4.6 mm, 5 μm particle size); Hichrom Ltd.	Aqueous phase: 0.02 M MOPS buffer, pH 7.2 (25-70%) Organic phase: MeOH (30-75%)	HPLC mode: isocratic Detection: UV-Vis (215 and 500 nm) or RID	57 Terpenoids including monoterpene hydrocarbons and oxygenated terpenes: alcohols, aldehydes, ketones, acetates (1.81 < logP < 4.48)	log _{k_w} , logP	[118]
Gemini C18 hybrid silica-based columns (150 mm × 4.6 mm and 50 mm × 4.6 mm, 5 μm particle size); Phenomenex Inc.	Aqueous phase: (1) 20 mM Na ₂ HPO ₄ , pH 3.0 (2) 20 mM Na ₂ HPO ₄ , pH 7.0 (3) 20 mM Na ₂ B ₄ O ₇ , pH 10.0 Organic phase: MeOH (40-55%)	HPLC mode: isocratic Detection: UV (254 nm)	28 Pharmaceuticals including: basic (local anesthetics, β-blockers), acidic (non-steroidal anti-inflammatory drugs) and neutral (steroid hormones) drugs.	log _{k_w} , S	[86]
Kromasil C18 (250 mm × 4.6 mm, 5 μm particle size); Akzo Nobel / Eka Chemicals Inc.	Aqueous phase: H ₂ O (20%) Organic phase: MeOH (80%)	HPLC mode: isocratic Detection: UV-Vis (λ _{max} for each compound) Dead time marker: NaNO ₃	21 Persistent organic pollutants (POPs; 2.0 < logP < 7.0) including model compounds and synthetic organochlorine pesticides (DDT and DDT-related compounds)	log _{k_w} , logP	[119]
XBridge-C18 column packed with bridged ethylene hybrid (BEH) particles (50 mm × 3 mm, 2.5 μm particle size); Waters Corporation	Aqueous phase: (1) 10 mM HCOONH ₄ (pH: 2.5, 3.3, 4.1, 8.9, 9.7) (2) 10 mM CH ₃ COONH ₄ (pH: 4.9, 5.8) (3) 10 mM NH ₄ HCO ₃ (pH: 6.8, 10.5) Organic phase: MeOH	HPLC mode: two pH/organic modifier gradient sets Detection: ESI-TOF-MS (range 50-1200 m/z) Dead volume marker: citric acid	40 drugs including antibiotics, antidepressant, β-blockers, anti-arrhythmic agents, anticoagulants, antipsychotics, hypertensive drugs, anesthetic drugs, antispasmodic drugs, anti-inflammatory drugs, antifungal drugs, analgesic and antipyretic drugs	log _{k_w} , logP, logD, pK _a *	[120]
LiChroCART Purosphere RP-18e (125 mm × 3 mm, 5 μm particle size), Zorbax Eclipse XDBC8 (150 mm × 4.6 mm, 5 μm particle size), Discovery RP-Amide C16 (150 mm × 4.6 mm, 5 μm particle size), LiChrospher 100 CN (250 mm × 4 mm, 5 μm particle size), and Kinetex PFP (150 mm × 2.1 mm, 2.6 μm particle size)	Aqueous phase: 0.1% HCOOH Organic phase: MeOH (50-70%)	HPLC mode: isocratic Detection: UV (254 nm) Dead time marker: uracil	22 antioxidant compounds including phenolic acids, flavonoids, anthocyanins, xantonoids, proanthocyanidins	log _{k_w} , log _{k_w}	[121]
Luna C18(2) (150 mm × 4.6 mm, 5 μm particle size), Candeza CD-C18 (150 mm × 4.6 mm, 3 μm particle size), TSK-gel ODS-80TS (150 mm × 4.6 mm, 5 μm	Aqueous phase: 0.1% HCOOH Organic phase: ACN with 0.1% HCOOH	HPLC mode: gradient Detection: UV (254 nm)	21 antitumor acridinone (imidazoacridinone and triazoloacridinone) derivatives	log _{k_w} , logP	[122]



particle size), Ascentis C18 (150 mm × 4.6 mm, 5 μm particle size), Unison UK-C18 (150 mm × 4.6 mm, 3 μm particle size), and Zorbax SB-C8 (75 mm × 4.6 mm, 3.5 μm particle size)					
LiChroCART LiChrospher RP-18e (250 mm × 4 mm, 5 μm particle size), LiChroCART Purosphere RP-18e (125 mm × 3 mm, 5 μm particle size), Zorbax Eclipse XDBC8 (150 mm × 4.6 mm, 5 μm particle size)	Aqueous phase: (1) H ₂ O with NH ₃ aq, pH 9.6 (2) H ₂ O with HCOOH, pH 2.8 Organic phase: MeOH	HPLC mode: isocratic Detection: UV (230 nm), MS Dead time marker: acetone	10 compounds with increased toxicity (mycotoxins and alkaloids) and 12 amines with important biological activity	k, k ₀ , S, PC1/k	[123]
POLYMER-BASED COLUMNS					
PRP-1 column (150 mm × 4.1 mm, 10 μm particle size); Hamilton company and ACT-1 (150 mm × 4.6 mm, 10 μm particle size); Interaction chemicals	Aqueous phase: 0.1 M CH ₃ COONH ₄ , pH 4.6 (35 or 30%) Organic phase: ACN (65 or 70%)	HPLC mode: isocratic Detection: UV (210, 230 or 254 nm) Dead time marker: NaNO ₃	40 Compounds from different classes: non-H bonders, single amphiprotics (with 1 hydroxyl or amide substituent), and double amphiprotics	logk	[124]
Asahipak ODP 50-4D (150 mm × 4.6 mm, 5 μm particle size); Shodex Group, Showa Denko K.K.	<u>HPLC experiments</u> Aqueous phase: (1) H ₂ O (2) 20 mM NH ₄ H ₂ PO ₄ , pH 2.0 (3) 20 mM NH ₄ H ₂ PO ₄ , pH 10.0 Organic phase: MeOH and ACN for experiments with each of the aqueous phases <u>IP-HPLC experiments</u> Aqueous phase: (1) 20 mM NH ₄ H ₂ PO ₄ , pH 7.0 (2) 20 mM NH ₄ H ₂ PO ₄ , pH 7.0 + 10 mM TBAB Organic phase: MeOH	HPLC mode: isocratic and gradient IP-HPLC mode: isocratic Detection: UV-Vis (λ _{max} for each compound)	72 Chemical compounds including 24 neutral compounds, 20 weak acid compounds, 14 strong acid compounds, 14 basic compounds	logk _w , CHI, k _g	[87]
C18-derivatized PS-DVB column (Act-I, 50 mm length); Interaction chemicals	Aqueous phase: H ₂ O (40%) Organic phase: MeOH (60%)	HPLC mode: isocratic Detection: UV (230 nm) Dead time marker: NaNO ₃	50 Different chemical compounds including non-hydrogen bonding compounds, acids/alcohols, bases, and hydrogen bonding acceptors (-0.20 < logP < 3.88)	logk, logP	[125]
ODP-50 column (20 mm × 4 mm, 5 μm particle size); Supelco	Aqueous phase: (1) 26 mM CF ₃ COOH, pH 2.0 (2) 10 mM Na ₃ PO ₄ , pH 7.0 (3) 10 mM Na ₃ PO ₄ , pH 10.0	HPLC mode: gradient Detection: UV (260, 285 nm)	16 Compounds with antimicrobial activity from group of 3(2 <i>H</i>)-isothiazolones	logP	[126]



	Organic phase: MeOH				
PRP-1 column (150 mm × 4.6 mm, 5 μm particle size); Hamilton company	Aqueous phase: 25 mM CH ₃ COONH ₄ buffer of pH (1) 4.5, (2) 7.2, (3) 9.8 Organic phase: ACN	HPLC mode: isocratic and gradient Detection: UV or ELSD	21 Commercially available drugs and 24 biologically active marine natural products	log _{k_w} , CHI, logP	[77]
ODP-50 column (20 mm × 4 mm, 5 μm particle size); Supelco	Aqueous phase: 10 mM Na ₃ PO ₄ adjusted to pH (1) 2, (2) 7, (3) 10 Organic phase: MeOH	HPLC mode: gradient Detection: UV (260-285 nm)	120 Different chemical compounds including 26 pharmaceuticals, 24 fungicides, 25 herbicides, 25 insecticides and 20 miscellaneous	logP	[90]
Supelguard ODP-50 column (20 mm × 4 mm); Supelco	Aqueous phase: 15 mM potassium phosphate buffer adjusted to pH (1) 2.0 (H ₃ PO ₄), (2) 7.4, (3) 11.0 (KOH) Organic phase: MeOH	HPLC mode: gradient Detection: UV (230, 260 nm)	15 β-blockers and structurally related compounds	logD	[89]
Asahipak ODP-50-4B column (50 mm × 4.6 mm, 5 μm particle size); Asahi Chemicals	Aqueous phase: 20 mM phosphate buffer prepared using <i>n</i> -octanol - saturated H ₂ O and adjusted to pH (1) 3.0, (2) 4.0, (3) 7.0 Organic phase: MeOH with addition of 0.25% <i>n</i> -octanol	HPLC mode: isocratic Detection: UV-Vis (λ _{max} for each compound) Dead time marker: uracil	Set of 41 compounds including model solutes (13 acids, 8 neutrals, 5 bases) and 15 drugs (-0.69 < logP < 4.80)	logk, log _{k_w} , S	[88]
PLRP-S column (50 mm × 4.6 mm, 5 μm particle size), Agilent	Aqueous phase: 20 mM CH ₃ COONH ₄ , pH 7.0 Organic phase: ACN (10, 15 and 20%)	HPLC mode: isocratic Detection: UV-Vis	Amyloid β-peptides: Aβ ₁₂₋₂₈ and Aβ ₂₅₋₃₅	logk	[127]
PLRP-S column (50 mm × 4.6 mm, 5 μm particle size), Agilent	Aqueous phase (pH range 2-11): (1) 0.1% formate buffer (2) 0.1% CH ₃ COONH ₄ (3) 10 mM triethylamine Organic phase: ACN (80%)	HPLC mode: isocratic Detection: UV (215, 254, 280, 310 nm) and MS Dead time marker: astemizole (pH ~ 2) valsartan (pH ~ 10)	3 Sets of compounds: (1) 44 neutral compounds (simple organic molecules, commercial drugs), (2) 10 compounds (5 pairs) capable and incapable to form intramolecular hydrogen bonds, (3) 76 commercial drugs	logk	[128]
BIOMIMETIC COLUMNS					
IAM.PC.DD2 column (150 mm × 4.6 mm, 10 μm particle size); Regis Technologies Inc.	Aqueous phase: (1) 0.1% (v/v) HCOOH, pH 2.8 (2) 10 mM CH ₃ COONH ₄ , pH 7.0 Organic phase: MeOH	HPLC mode: gradient Detection: UV (230, 254 nm)	32 Analogs of 4-hydroxycoumarin (biologically active compounds)	CHI	[129]



IAM.PC.MG (150 mm × 4.6 mm, 10 μm particle size) and IAM.PC.DD2 (100 mm × 4.6 mm, 10 μm particle size); Regis Technologies Inc.	Aqueous phase: 0.1 M phosphate buffer of pH (1) 7.0, (2) 5.5 Organic phase: ACN (15-30% if required)	HPLC mode: isocratic Detection: UV (λ_{\max} for each compound)	10 Quinolone antibacterial agents, including both acidic and zwitterionic congeners	logk, logk _w , logP	[130]
IAM.PC.MG (150 mm × 4.6 mm, 10 μm particle size) and IAM.PC.DD2 (30 mm × 4.6 mm, 12 μm particle size) columns; Regis Technologies Inc., ChromTech chiral-HSA and ChromTech chiral-AGP (50 mm × 4 mm, 5 μm particle size) columns; Supelco	<u>For IAM columns:</u> (1) High purity water (2) 20 mM MOPS with pH of 4.2 and 7.4 (3) PBS with pH of 4.2 and 7.4 (4) 50 mM CH ₃ COONH ₄ , pH 7.4 <u>For the HSA and AGP columns:</u> (1) High purity water (2) PBS with pH of 4.2 (only AGP), 5.0 (only HSA) and 7.0 (3) 50 mM CH ₃ COONH ₄ , pH 7.0	HPLC mode: isocratic Detection: UV-Vis (205 nm)	11 Selenium species including methylseleninic acid, methylselenocysteine, dimethylselenourea, selenites Se(IV), selenates Se(VI), seleno-DL-methionine, L-selenocystine, selenocystamine, selenourea, dimethyl selenide, dimethyl diselenide	logk, logk _w , logD	[5,131]
IAM.PC.DD2 (100 mm × 3 mm), Chiralpack-HSA and Chiralpack -AGP (50 mm × 3 mm); Regis Technologies Inc.	Aqueous phase: 50 mM CH ₃ COONH ₄ , pH 7.4 Organic phase: ACN (IAM column), IPA (HSA and AGP columns)	HPLC mode: gradient Detection: UV (254 nm)	117 Marketed drugs	logk, logP	[102]
Chiral-HSA and Chiral-AGP (100 mm × 4 mm); Chrom Tech Ltd.	<u>For HSA column:</u> Aqueous phase: 10 mM phosphate buffer, pH 7.0 Organic phase: IPA (20% required only for nebivolol) <u>For AGP column:</u> Aqueous phase: 10 mM phosphate buffer, pH 7.0 (75% or 90%) Organic phase: MeOH	HPLC mode: isocratic Detection: UV (λ_{\max} for each compound)	13 β-blockers (enantiomers) including acebutolol, alprenolol, atenolol, betaxolol, labetalol, metoprolol, nadolol, nebivolol, oxprenolol, pindolol, propranolol, sotalol, and timolol	logk, logk _w , logP, logD	[91]
Chiral-HSA (50 mm × 3 mm); Chrom Tech Ltd., and RexChrom IAM PC2 (CH ₂) ₁₂ (150 mm × 4.6 mm); Fisher Scientific	Aqueous phase: 50 mM CH ₃ COONH ₄ , pH 7.4 Organic phase: IPA (HSA column), ACN (IAM column)	HPLC mode: gradient Detection: UV (230, 254 nm)	68 Drug molecules	logK _{HSA} , CHI _{IAM}	[73,101]



Chiral-HSA (50 mm × 3 mm); Chrom Tech Ltd.	Aqueous phase: PBS, 0.157 M K ⁺ /Na ⁺ , pH 7.0 Organic phase: ACN and IPA (5-20%)	HPLC mode: isocratic Detection: UV (220, 254 nm)	63 Structurally diverse basic, acidic and neutral drugs	logk, S, logk _w	[132]
IAM.PC.MG (150 mm × 4.6 mm) and IAM.PC.DD2 (100 mm × 4.6 mm); Regis Technologies Inc.	Aqueous phase: 0.1 M phosphate buffer, pH 7.0 Organic phase: ACN (10-30% if required)	HPLC mode: isocratic Detection: UV (λ _{max} for each compound)	14 Basic drugs spanning a wide lipophilicity range	logk, logk _w	[133]
IAM.PC.MG (150 mm × 4.6 mm); Regis Technologies Inc.	Aqueous phase: 16 mM phosphate buffer, pH 7.4 Organic phase: ACN (4-27%)	HPLC mode: isocratic Detection: UV (λ _{max} for each compound; 225-290 nm)	11 Arylpropionic non-steroidal anti-inflammatory drugs	logk, logk _w	[134]
IAM.PC.DD2 (100 mm × 4.6 mm); Regis Technologies Inc.	Aqueous phase: 10 mM phosphate buffer of pH (1) 3.0, (2) 5.0, (3) 7.4 Organic phase: ACN (≤ 30% if required)	HPLC mode: isocratic Detection: UV or MS/MS	86 Monoprotic positively charged amines including monopolar amines, dipolar amines, amines with polar N moieties, polycyclic amine structures, and complex multifunctional amine structures	logk, logk _w	[135]

ACN – acetonitrile; AGP – α₁-acid glycoprotein; Brij 35 – polyoxyethylene lauryl ether; CTAB – cetyltrimethylammonium bromide; DDT – dichlorodiphenyl-trichloroethane; DMSO – dimethyl sulfoxide; DVB – divinylbenzene; ELSD – evaporative light scattering detection; ESI-TOF-MS – electrospray ionization time-of-flight mass spectrometry; HSA – human serum albumin; IPA – isopropyl alcohol; IP-HPLC – ion-pair high performance liquid chromatography; LI – lipophilicity index; MeOH – methanol; MOPS – 4-morpholinepropanesulfonic acid; MS – mass spectrometry; PBS – phosphate buffer saline; PS – polystyrene; RID – refractive index detector; SDS – sodium dodecyl sulfate; TBAB – tetrabutylammonium bromide; THF – tetrahydrofuran; TMAC – tetramethylammonium chloride; * possibility to determine acid dissociation constant (pK_a) in the same HPLC run

438

439

440

441

442

443

444



445 3.1.2.2. HPLC procedures for lipophilicity assessment

446 As summarized in details in recent reviews [21,23,67,68,76], the HPLC-based procedures in isocratic
447 and gradient elution mode have been widely used for determination of various LIs, mainly $\log k_w$, ϕ_0
448 and S (slope of the linear relationship between the organic solvent concentration (ϕ) and the $\log k$).
449 Therefore, here only the main principles of most commonly applied HPLC approaches will be
450 discussed.

451 Most of the reported procedures are based on isocratic measurements of compounds retention that is
452 normalized by column dead time and expressed as retention factor (see Fig.4). In isocratic method,
453 several HPLC analyses at different MP compositions (min. 4 various concentrations of organic
454 modifier) must be carried out for each compound, which requires preliminary experiments and is more
455 time-consuming. The obtained results should be extrapolated to the same MP composition, normally
456 to pure aqueous phase. The Snyder-Soczewinski equation (Eq. 9) is the most commonly used for
457 such extrapolation [136]:

$$458 \log k = -S \cdot \phi + \log k_w \quad (9)$$

459 Although this relationship is non-linear in the full range of organic modifier concentration, a good
460 approximation within the working limits of $-0.5 < \log k < 1.5$ is ensured [68]. If necessary, a quadratic
461 model (Eq. 10) can be applied:

$$462 \log k = A \cdot \phi^2 + B \cdot \phi + \log k_w \quad (10)$$

463 where A and B are regression coefficients. $\log k_w$ is regarded as the most representative LI, since its
464 value is of the same order of magnitude as $\log P$ or $\log D$. Both isocratic retention factors ($\log k$ or
465 $\log k_w$) are directly correlated to n-octanol-water $\log P/\log D$ via Collander equation (Eq. 11):

$$466 \log P/\log D = a \cdot \log k_w + b \quad (11)$$

467 where a and b are linear regression coefficients determined by analyzing a set of standard
468 compounds according to OECD guidelines [69].

469 Assessment of LIs of highly lipophilic compounds using standard polycratic approach is difficult or
470 rather impossible due to RTs being too long and thus analysis becomes very time-consuming and
471 labor-intensive. Therefore, a new approach to determine $\log k_w$ through the correlation with $\log k$ was
472 introduced [137]. As the S and $\log k_w$ parameters indicating mechanism of retention give a linear
473 relationship for structurally related compounds (see Eq. 12) [28], the $\log k_w$ value can be evaluated



474 based on $\log k$ measured only for the corresponding organic modifier concentration according to the
 475 following formula (Eq. 13):

$$476 \quad S = a \cdot \log k_w + b \quad (12)$$

$$477 \quad \log k_w = (b \cdot \varphi + \log k) / (1 - a \cdot \varphi) \quad (13)$$

478 where a and b correspond to the slope and the intercept, respectively.

479 In order to speed up the lipophilicity evaluation, various gradient HPLC methods have been proposed,
 480 and as a result a new LI namely CHI was introduced by Valkó et al. [138,139]. It links the isocratic and
 481 gradient retention together and represents the volume of organic modifier in MP for which the
 482 amounts of solute distributed between two phases are equal ($k = 1$, $\log k = 0$). The CHI is computed
 483 as follows:

$$484 \quad \varphi_0 = -\log k_w / S \quad (14)$$

485 It has been shown that gradient RTs (t_{Rg}) correlate well with isocratically determined CHI values and
 486 thus give a straight line when plotted against the CHIs obtained for given set of standards [70,138].
 487 The slope (a) and the intercept (b) of the calibration equation (Eq. 15) are used to convert t_{Rg} of
 488 analytes to CHI scale (range of 0-100) that is useful for inter-laboratory study and database creation:

$$489 \quad \varphi_0 (\text{CHI}) = a \cdot t_{Rg} + b \quad (15)$$

490 The CHI values can also be converted to $\log P$ scale. However, the best correlation was observed for
 491 neutral form of compounds. Considering the H-bond acidity or the H-bond count terms, the
 492 relationship between $\log P / \log D$ and CHI can be improved as reported by Valkó et al. [70].

493 As an alternative LI, an apparent capacity factor (k_g) was introduced by Krass et al. [140] and defined
 494 as follows:

$$495 \quad k_g = (V_g - V_d - V_m) / V_m \quad (16)$$

496 where V_g is gradient retention volume, V_d is system delay volume and V_m is column dead volume. A
 497 good correlation between k_g and $\log k_w$ obtained in a series of isocratic HPLC runs was reported.

498 Nowadays, the rapid-gradient RP-HPLC methods using high flow rate and short columns to reduce
 499 the analysis time (up to ~5 min) with a negligible loss of resolution have been widely applied for the
 500 lipophilicity assessment. The use of MS detection allows to determine CHIs for mixture of compounds,
 501 which further accelerates the experimental work [141]. Another improvement has been proposed by
 502 Wiczling et al. [120,142], who employed time-of-flight MS to enlarge the number of analytes in



503 individual HPLC run and to facilitate their identification in complex mixture. They have developed a
504 double pH/methanol gradient procedure for the simultaneous determination of $\log k_w$ and pK_a values
505 based on two gradient RTs of a compound (one is an organic phase, the other is a pH gradient), with
506 a screening rate of about 100 compounds/day.

507 Summarizing, using gradient RP-HPLC methods, reproducible LIs can be obtained in a high-
508 throughput way. The current trend is also focused on the use of chemometric tools, such as principal
509 component analysis, to extract the meaningful and interpretable features from the multivariate HPLC
510 raw data on lipophilicity and then provide new highly descriptive LIs (i.e. principal components and
511 their derivatives) [26,121].

512 3.2. Electroseparation methods

513 Electroseparation techniques used to determine the lipophilic properties are based generally on
514 capillary electrophoresis (CE). In this method, analytes migrate through electrolyte solutions (buffers
515 with pH adjusted to certain values) under the influence of electric field. They can be separated in two
516 different ways: according to ionic mobility or/and partitioning into an alternate phase via non-covalent
517 interactions [143,144]. Migration of the analytes is confined by the sum of two factors: electroosmotic
518 mobility (μ_{eo}) and intrinsic electrophoretic mobility (μ_{ep}). This limitation is caused by the action of
519 electroosmotic flow (EOF) of the buffer solution, which is defined as a bulk liquid motion that results
520 when the external electric field interacts with the net surplus of charged ions in the diffuse part of the
521 electrical double layer [145,146]. The velocity of the EOF (u_{eo}) can be defined as:

$$522 \quad u_{eo} = \mu_{eo} \cdot E \quad (17)$$

523 where E is the intensity of the applied electric field (V/m). The electroosmotic mobility (μ_{eo}) may be
524 experimentally determined by measuring the migration time of a neutral analyte.

525 The use of CE has few advantages such as small amount of compounds required, speed and
526 relatively easy automation and low consumption of solvents. In many cases CE is used as an
527 alternative or complementary technique to HPLC due to its high separation efficiency [6,53,147].
528 Hence, CE remains to play an important role in separation of medium size molecules (e.g. peptides,
529 oligosaccharides and oligonucleotides), as well as in analysis of large macromolecules, such as
530 polysaccharides, nucleic acids and synthetic polyelectrolytes. [143,148,149].

531 For analysis of both charged and neutral compounds electrokinetic chromatography (EKC) methods,
532 including micellar electrokinetic chromatography (MEKC), microemulsion electrokinetic
533 chromatography (MEEKC) and vesicular electrokinetic chromatography (VEKC) are applied [150].
534 MEKC has gained in popularity for the indirect estimation of logP values of small molecules. The main
535 difference between MEKC and CE is that the solution contains a surfactant, which concentration is
536 greater than critical micelle concentration (CMC), so the concentration of monomers reaches a critical
537 value when only micelles are present. These micelles are the pseudo-SP and the analytes are
538 separated by differential partitioning between them and surrounding buffer solution (MP) [151].
539 Usually, MEKC is performed in open capillaries under the alkaline conditions to generate a strong
540 EOF. Anionic micelles of SDS is the most common surfactant for MEKC systems and it was the first
541 surfactant used for logP determination [152]. In comparison with n-octanol/water partition system, the
542 advantage of MEKC results from the large difference in hydrogen-bond basicity, and to a lesser
543 extent, dipolarity/polarizability, for partition into SDS micelles. Although, a better partition model is
544 provided by sodium N-dodecyl-N-methyltaurine (SDMT), this surfactant has not been used for
545 estimating logP [6]. However, Ibrahim et al.[153] investigated the use of bile salts as a pseudo-SP in
546 MEKC. The results showed that sodium deoxycholate (SDC) was the most appropriate surfactant
547 used to estimate lipophilic properties of fungicides. Due to the fact that bile salts can be found in
548 biological systems, the SDC-MEKC method is considered to be environmentally friendly. More
549 detailed information on the MEKC principle and the reagents used are summarized by Terabe [151]
550 and Silva[152]. As in the case of LC, determination of logP is based on the relationship between this
551 coefficient and the retention factor [154]. This factor in MEKC technique may be defined as (Eq. 18):

$$552 \quad k' = (t_R - t_0)/(t_0 \cdot (1 - (t_R/t_{mc}))) \quad (18)$$

553 where t_R , t_0 and t_{mc} are the migration times of the solute, the EOF marker (e.g. methanol), and the
554 micelle marker (e.g. Sudan III or Sudan IV), respectively [151]. Compared to SFM, MEKC has the
555 advantages of speed, wide dynamic range, high sample throughput and small sample size [150,151].

556 For indirect determination of logP values MEEKC can also be applied. This technique can be seen as
557 extension of MEKC, however in this case the microemulsion is used as migrating pseudo-SP.
558 Microemulsions are immiscible oils droplets in water (usually heptane or octane droplets) that are
559 stabilized by co-surfactants and surfactants situated at the surface of the droplet [147,155,156]. The
560 most commonly used surfactant and co-surfactant in MEEKC are SDS and 1-butanol, respectively



561 [6,156]. The mechanism of separation in MEEKC is based on differential partitioning of analyte into
562 migrating microemulsion, which is related to analyte hydrophobicity. Therefore, the migration time of
563 analyte is proportional to its hydrophobicity, so its retention factor (k') is related to values of $\log P$. To
564 determine the k' value it is necessary to precisely measure the migration time of EOF marker (t_0) and
565 microemulsion marker (t_{me}), such as octanophenone, along with analyte (t_R) and then to calculate the
566 retention factor from the following formula [150] (Eq. 19):

$$567 \quad k' = (t_R - t_0) / (t_0 \cdot (1 - (t_R/t_{me}))) \quad (19)$$

568 In order to determine $\log P$ values, Xia et al. [157] developed novel MEEKC approach based on peak-
569 shift assay. In comparison to conventional approach, this method provides the $\log P$ values of the
570 compounds without the use of reference substances with known $\log P$ values reported in the literature.
571 Fernández- Pumarega et al. [158] presented the applicability of MEEKC in estimation of $\log D$ of acidic
572 drugs at several ionization degrees. They reported that the overestimation of $\log D$ was observed only
573 at degree of ionization higher than 99.5%. However, further research is needed to check if this
574 behavior can occur with other compounds. This paper showed that MEEKC can be an alternative to
575 other approaches used in lipophilicity assessment. Compared to MEKC, in MEEKC better
576 solubilization properties for water insoluble compounds has been observed [156,159]. Furthermore,
577 the hydrogen bond effects that affect the partitioning behavior of some solutes during lipophilicity
578 determination are minimal in MEEKC compared to RP-HPLC or MEKC. This may be due to the
579 addition of co-surfactant (1-butanol) that minimizes electrostatic interactions as reported by Ishihama
580 et al. [160]. They also showed that MEEKC provides better correlation of retention factor with $\log P$
581 determined by SFM than MEKC and RP-HPLC methods for which the hydrogen acceptor and
582 hydrogen donor effects must be considered. In addition, some limitations of SFM (e.g. large amount
583 of high purity sample, lack of automation) and chromatographic methods (e.g. limited pH range,
584 lifetime of SP) are overcome in the MEEKC [155].

585 Another EKC technique applied for $\log P$ determination is VEKC. Vesicles are self-assembling,
586 organized structures that contain continuous bilayer of monomers and enclose an aqueous core
587 region used as potential models of synthetic membranes. In nature, this formation occurs through the
588 aggregation of phospholipids to form liposomes [6]. Hence, vesicles synthesized from phospholipid
589 aggregates may be used as pseudo-SP in VEKC. These vesicles are inherently physiological, but
590 they are stable only in multilamellar form. Due to the fact that in EKC analysis the monolamellar forms



591 are preferred, the use of liposomes requires some additional laborious preparation procedures
592 allowing the production of monolayer vesicles [161]. However, the vesicles can also be synthesized
593 using oppositely charged surfactants and double ionic surfactants, such as bis(2-ethylhexyl)sodium
594 sulfosuccinate in a phosphate buffer containing 10% (v/v) methanol (an anionic, double chain
595 surfactant known as Aerosol OT or AOT) or hexadecyltrimethylammonium bromide-sodium octyl
596 sulfate (double ionic surfactant, known as CTAMB-SOS) [6,150]. Jiang et al. [162] investigated the
597 influence of the molar ratio of cationic to anionic surfactants on the vesicle properties and the
598 performance of VEKC. It is well known that due to the electrostatic attractions among oppositely
599 charged head groups of ionic surfactants and the hydrophobic interaction of their hydrocarbon tails
600 the strong synergistic effects may occur. Some of physical properties of vesicles can be modified by
601 changing the ratio of ionic surfactants. These changes affect the performance of VEKC. It has been
602 reported that the molar ratio of 3:7 and 5:5 systems used as pseudo-SP had similar selectivity.
603 However, the second system showed rapid and efficient separation for nonpolar substances [162].
604 Because of the similarity of surfactant vesicles and liposomes, both VEKC systems may be used not
605 only as separation models for estimation of logP of various neutral and charged compounds, but also
606 as a model for environmental and biological partitioning (e.g. permeability, diffusion or membrane
607 transport) [6,163–165]. To obtain logP values, the retention factor (k') determined by VEKC technique
608 should be calculated according to following formula (Eq. 20):

$$609 \quad k' = (t_R - t_0)/(t_0 \cdot (1 - (t_R/t_v))) \quad (20)$$

610 where t_v , t_R and t_0 are the migration times of vesicle marker (e.g. dodecanophenone or octylbenzene),
611 the solute and the EOF marker, respectively [163]. The use of VEKC for determination of n-octanol-
612 water partition coefficients has similar advantages to MEKC. However, it is difficult to obtain
613 reproducible results using this technique [150].

614 3.3. Electroanalytical methods

615 A variety of electrochemical methods have been developed, but the most frequently chosen methods
616 for lipophilicity assessment are potentiometric and voltammetric ones [166]. Potentiometric methods
617 were described for the first time in 1952 and since that time, they have been applied in different
618 branches of science and industry. The determination of lipophilic profile of compound directly from a
619 single acid-base titration in dual-phase partition solvent system is fast, however, it is necessary to
620 know the acid dissociation constant (pK_a) of tested compounds in case of using some of these

621 methods. Potentiometric methods create a good alternative to SFM especially in the case of acidic or
622 basic compounds. Furthermore, the use of these methods enable to determine the logP in range of -1
623 to 8. Unfortunately, they require a relatively large amount of samples [27,32].

624 Classical potentiometric titration can be used for the evaluation of the partition of ionizable
625 compounds or ion-paired substances into the organic phase. Simple titration procedure, together with
626 calculation of pK_a values involved the ionization of water in n-octanol, has been proposed by Scherrer
627 and Donovan [167]. During the measurement, the pK_a of analytes is determined by adding high
628 precision titrators. A potentiometric titration procedure in KCl/water-saturated n-octanol provides a link
629 to logP through the thermodynamic cycle of ionization and partitioning (Fig. 5). The use of this titration
630 method in order to apply it for the determination of substituent ion pair stabilization values (IPS) may
631 give more accurate data concerning logD calculations.

632 The greatest advantage of potentiometric titration over other methods is the independence of
633 measurements from the magnitude of logP value. In the same time, a reproducibility of a few
634 hundredths of a logP in the calculated difference between $\log P^N$ (neutral forms) and $\log P^I$ (ionized
635 forms) is maintained.

636 Titrations in KCl/water-saturated n-octanol provide essential data to advance our understanding of ion
637 pair partitioning in n-octanol, but the ultimate goal of the lipophilicity studies is the application of this
638 knowledge to the anisotropic world of cells, membranes, proteins, and nucleic acids [23,167].

639 Cyclic voltammetry (CV) has been used for the indirect determination of the lipophilicity of organic
640 salts. Generally, typical CV system consists of four-electrode potentiostat, the aqueous phase and
641 nitrobenzene or 1,2-dichloroethane (EDC) as the organic phase [50,168]. Bouchard et. al. proposed
642 to use CV for examination of the lipophilicity of quaternary ammonium drugs and proved that the
643 partition of some ions is influenced by Galvani potential difference, not ion-pairing phenomenon. The
644 obtained values of standard water-EDC partition coefficient of ions correlated well ($R^2 = 0.94$) with
645 logP values of neutral molecular structures closest to these ions that were calculated by computer
646 algorithms [168]. In contrast to traditional SFM, the partition coefficient determined by CV does not
647 depend on experimental conditions. Furthermore, the use of this technique enables to estimate very
648 low logP values ranging from - 8 to 1. The main disadvantages of CV are the limited number of



649 solvent systems that can be applied for lipophilicity determination and the large amount of sample
650 required (1-10 mg) [50,53,168,169].

651 **4. Conclusion**

652 Lipophilicity is an essential physicochemical property, which affects biological activities, assimilation
653 and environmental fate of compounds. Despite the importance of lipophilicity, its evaluation is still
654 problematic and constantly attracts researchers' attention. Nowadays, classical methods are almost
655 completely replaced by instrumental ones, in particular separation techniques. Compared with the
656 classical approach, the use of chromatographic or EKC methods does not require a long analysis time
657 and a large amount of high purity samples. The purity of the sample may be problematic for unstable
658 analytes and may lead to false results. Since only retention factors must be determined using
659 separation techniques, the analytical quantification is not required. This drawback of classical liquid-
660 liquid system (i.e. SFM) is really serious in the case of highly lipophilic or sparingly soluble
661 compounds due to the need for a highly sensitive quantification system. In turn, potentiometric
662 titration as fully automated and time-saving instrumental technique is only applicable to acidic and
663 basic compounds of high purity and may not be suitable for highly hydrophobic molecules due to
664 solubility problems. Chromatographic methods, especially TLC and fast HPLC, considered as
665 economical and environmentally friendly solutions, can be used to determine lipophilicity of both
666 neutral and dissociable compounds. However, the pH and composition of the mobile phase should be
667 carefully selected in order to ensure that the compound is in its neutral form. Furthermore, new
668 solutions have been introduced to reduce the limitations of indirect separation-based methods,
669 including employment of new HPLC columns, addition of masking agents to mobile phase,
670 modifications of CE, application of surfactants in TLC experiments, and development of new
671 lipophilicity indices. The gradient HPLC methods proposed as alternative to isocratic ones give other
672 additional advantages, particularly speed up experimental process and reduce costs. However, there
673 is still an urgent need for valid, standardized and high-throughput procedures to determine the
674 lipophilicity of chemical compounds.

675 Future trends may also include (i) design of new biomimetic SPs through immobilization of important
676 biomolecules or binding similar functional groups to the silica surface in order to mimic partitioning in
677 different biological and environmental systems thus help to better understand these phenomena, (ii)

678 development of new biological partition/distribution models using well designed HPLC retention
679 properties, (iii) application of chemometric approaches to provide new highly descriptive LIs and build
680 large data bases for comparison purposes, (iv) estimation of potential kinetic aspects of partitioning
681 based on changes in the symmetry and width of chromatographic peak as a function of the MP flow
682 rate.

683 Acknowledgements

684 Project „Antioxidant Power Series as a tool rational design and assessment of health promoting
685 properties of functional food based on antioxidant phytochemicals” (number of the application
686 2014/14/A/ST4/00640) financed by National Science Centre, Poland in a programme „MAESTRO 6”.

687 References

- 688 [1] M. Nič, J. Jirá, B. Košata, A. Jenkins, A. McNaught, eds., IUPAC. Compendium of Chemical
689 Terminology. Gold Book., IUPAC, Research Triangle Park, NC, 2014. doi:10.1351/goldbook.
- 690 [2] C.A. Lipinski, F. Lombardo, B.W. Dominy, P.J. Feeney, Experimental and computational
691 approaches to estimate solubility and permeability in drug discovery and development, *Adv.*
692 *Drug Deliv. Rev.* 46 (2001) 3–26.
- 693 [3] C.T. Chiou, Environmental partitioning and contamination of organic compounds, *J. Chinese*
694 *Inst. Environ. Eng.* 13 (2003) 1–6.
- 695 [4] M.G. Montalbán, M. Collado-González, R. Trigo, F.G. Díaz Baños, G. Vllora, Experimental
696 Measurements of Octanol-Water Partition Coefficients of Ionic Liquids, *J. Adv. Chem. Eng.* 5
697 (2015) 133. doi:10.4172/2090-4568.1000.
- 698 [5] F. Tsopelas, A.T. Kakoulidou, M. Ochsenkühn-Petropoulou, Lipophilicity, biomimetic retention
699 profile and antioxidant activity of selenium species, *Microchem. J.* 110 (2013) 711–718.
700 doi:10.1016/j.microc.2013.08.009.
- 701 [6] S.K. Poole, C.F. Poole, Separation methods for estimating octanol-water partition coefficients,
702 *J. Chromatogr. B Anal. Technol. Biomed. Life Sci.* 797 (2003) 3–19.
703 doi:10.1016/j.jchromb.2003.08.032.
- 704 [7] M.V. Aguilar, C. Otero, eds., *Frontiers in Bioactive Compounds. Vol 2: At the Crossroads*
705 *Between Nutrition and Pharmacology*, BENTHAM SCIENCE PUBLISHERS, Sharjah, 2017.
706 doi:10.2174/97816810842991170201.
- 707 [8] I.-C. Hwang, H. Kwak, S.-J. Park, Determination and prediction of K_{ow} and dimensionless
708 Henry's constant (H) for 6 ether compounds at several temperatures, *J. Ind. Eng. Chem.* 16
709 (2010) 629–633. doi:10.1016/j.jiec.2010.03.003.
- 710 [9] C.J. van Leeuwen, T.G. Vermeire, *Risk Assessment of Chemicals: An Introduction*, in:
711 Springer Science & Business Media, Dordrecht, 2007: p. 686.
- 712 [10] W.M. Meylan, P.H. Howard, Estimating octanol–air partition coefficients with octanol–water
713 partition coefficients and Henry's law constants, *Chemosphere.* 61 (2005) 640–644.
714 doi:10.1016/J.CHEMOSPHERE.2005.03.029.
- 715 [11] M. Shoeib, T. Harner, Using measured octanol-air partition coefficients to explain
716 environmental partitioning of organochlorine pesticides., *Environ. Toxicol. Chem.* 21 (2002)

- 717 984–90. doi:10.1002/etc.5620210513.
- 718 [12] Y. Wang, J. Chen, X. Yang, F. Lyakurwa, X. Li, X. Qiao, In silico model for predicting soil
719 organic carbon normalized sorption coefficient (KOC) of organic chemicals, *Chemosphere*.
720 119 (2015) 438–444. doi:10.1016/J.CHEMOSPHERE.2014.07.007.
- 721 [13] I.T. Cousins, A.J. Beck, K.C. Jones, A review of the processes involved in the exchange of
722 semi-volatile organic compounds (SVOC) across the air–soil interface, *Sci. Total Environ.* 228
723 (1999) 5–24. doi:10.1016/S0048-9697(99)00015-7.
- 724 [14] Y.S. Tarahovsky, Y.A. Kim, E.A. Yagolnik, E.N. Muzafarov, Flavonoid–membrane interactions:
725 Involvement of flavonoid–metal complexes in raft signaling, *Biochim. Biophys. Acta -*
726 *Biomembr.* 1838 (2014) 1235–1246. doi:10.1016/J.BBAMEM.2014.01.021.
- 727 [15] D.J. McClements, Utilizing food effects to overcome challenges in delivery of lipophilic
728 bioactives: structural design of medical and functional foods, *Expert Opin. Drug Deliv.* 10
729 (2013) 1621–1632. doi:10.1517/17425247.2013.837448.
- 730 [16] J.A. Arnott, S.L. Planey, The influence of lipophilicity in drug discovery and design, *Expert*
731 *Opin. Drug Discov.* 7 (2012) 863–875. doi:10.1517/17460441.2012.714363.
- 732 [17] F. Lombardo, R.S. Obach, M.Y. Shalaeva, F. Gao, Prediction of volume of distribution values
733 in humans for neutral and basic drugs using physicochemical measurements and plasma
734 protein binding data., *J. Med. Chem.* 45 (2002) 2867–76.
735 <http://www.ncbi.nlm.nih.gov/pubmed/12061889> (accessed November 23, 2017).
- 736 [18] J. Viskupičová, M. Ondrejovič, E. Šturdík, Bioavailability and metabolism of flavonoids., *J.*
737 *Food Nutr. Res.* 47 (2008) 151–162. <http://www.ncbi.nlm.nih.gov/pubmed/21870774>.
- 738 [19] E. Kotake-Nara, Bioavailability and Functions of Lipophilic Components of Food, *Ann.*
739 *Pharmacol. Pharm. Ann Pharmacol Pharm.* 2 (2017) 1094.
- 740 [20] M.J. Rein, M. Renouf, C. Cruz-Hernandez, L. Actis-Goretta, S.K. Thakkar, M. da Silva Pinto,
741 Bioavailability of bioactive food compounds: A challenging journey to bioefficacy, *Br. J. Clin.*
742 *Pharmacol.* 75 (2013) 588–602. doi:10.1111/j.1365-2125.2012.04425.x.
- 743 [21] K.L. Valko, Lipophilicity and biomimetic properties measured by HPLC to support drug
744 discovery, *J. Pharm. Biomed. Anal.* 130 (2016) 35–54. doi:10.1016/j.jpba.2016.04.009.
- 745 [22] F. Tsopelas, C. Giaginis, A. Tsantili-Kakoulidou, Lipophilicity and biomimetic properties to
746 support drug discovery, *Expert Opin. Drug Discov.* 12 (2017) 885–896.
747 doi:10.1080/17460441.2017.1344210.
- 748 [23] E. Rutkowska, K. Pająk, K. Jóźwiak, Lipophilicity - Methods of determination and its role in
749 medicinal chemistry, *Acta Pol. Pharm. - Drug Res.* (2013) 3–18.
- 750 [24] R.D. Briciu, A. Kot-Wasik, A. Wasik, J. Namieśnik, C. Sârbu, The lipophilicity of artificial and
751 natural sweeteners estimated by reversed-phase thin-layer chromatography and computed by
752 various methods, *J. Chromatogr. A.* 1217 (2010) 3702–3706.
753 doi:10.1016/j.chroma.2010.03.057.
- 754 [25] K. Mazák, J. Vámos, A. Nemes, Á. Rácz, B. Noszál, Lipophilicity of vinpocetine and related
755 compounds characterized by reversed-phase thin-layer chromatography, *J. Chromatogr. A.*
756 996 (2003) 195–203. doi:10.1016/S0021-9673(03)00617-4.
- 757 [26] F. Tache, R.D. Naşcu-Briciu, C. Sârbu, F. Micăle, A. Medvedovici, Estimation of the lipophilic
758 character of flavonoids from the retention behavior in reversed phase liquid chromatography
759 on different stationary phases: A comparative study, *J. Pharm. Biomed. Anal.* 57 (2012) 82–
760 93. doi:10.1016/J.JPBA.2011.08.044.
- 761 [27] B. Testa, *Pharmacokinetic optimization in drug research: biological, physicochemical, and*
762 *computational strategies*, Verlag Helvetica Chimica Acta, 2001.

- 763 [28] D. Casoni, A. Kot-Wasik, J. Namieśnik, C. Sârbu, Lipophilicity data for some preservatives
764 estimated by reversed-phase liquid chromatography and different computation methods, *J.*
765 *Chromatogr. A.* 1216 (2009) 2456–2465. doi:10.1016/j.chroma.2009.01.029.
- 766 [29] X. Liu, H. Tanaka, A. Yamauchi, B. Testa, H. Chuman, Determination of lipophilicity by
767 reversed-phase high-performance liquid chromatography Influence of 1-octanol in the mobile
768 phase, *J. Chromatogr. A.* 1091 (2005) 51–59. doi:10.1016/j.chroma.2005.07.029.
- 769 [30] D. Lu, P. Chambers, P. Wipf, X.-Q. Xie, D. Englert, S. Weber, Lipophilicity screening of novel
770 drug-like compounds and comparison to clog P, *J. Chromatogr. A.* 1258 (2012) 161–167.
771 doi:10.1016/j.chroma.2012.07.078.
- 772 [31] C. Sârbu, D. Casoni, A. Kot-Wasik, A. Wasik, J. Namieśnik, Modeling of chromatographic
773 lipophilicity of food synthetic dyes estimated on different columns, *J. Sep. Sci.* 33 (2010) 2219–
774 2229. doi:10.1002/jssc.201000099.
- 775 [32] J.M. Pallicer, J. Sales, M. Rosés, C. Ràfols, E. Bosch, Lipophilicity assessment of basic drugs
776 (log P o/w determination) by a chromatographic method, *J. Chromatogr. A.* 1218 (2011) 6356–
777 6368. doi:10.1016/j.chroma.2011.07.002.
- 778 [33] F. Andrić, D. Bajusz, A. Rácz, S. Šegan, K. Héberger, Multivariate assessment of lipophilicity
779 scales—computational and reversed phase thin-layer chromatographic indices, *J. Pharm.*
780 *Biomed. Anal.* 127 (2016) 81–93. doi:10.1016/j.jpba.2016.04.001.
- 781 [34] L.G. Danielsson, Y.H. Zhang, Methods for determining n-octanol-water partition constants,
782 *TrAC - Trends Anal. Chem.* 15 (1996) 188–196. doi:10.1016/0165-9936(96)00003-9.
- 783 [35] D.E. Leahy, P.J. Taylor, A.R. Wait, Model Solvent Systems for QSAR Part I. Propylene Glycol
784 Dipelargonate (PGDP). A new Standard Solvent for use in Partition Coefficient Determination,
785 *Quant. Struct. Relationships.* 8 (1989) 17–31. doi:10.1002/qsar.19890080104.
- 786 [36] T. Hartmann, J. Schmitt, Lipophilicity - Beyond octanol/water: A short comparison of modern
787 technologies, *Drug Discov. Today Technol.* 1 (2004) 431–439.
788 doi:10.1016/j.ddtec.2004.10.006.
- 789 [37] Y.W. Alelyunas, L. Pelosi-Kilby, P. Turcotte, M.B. Kary, R.C. Spreen, A high throughput dried
790 DMSO Log D lipophilicity measurement based on 96-well shake-flask and atmospheric
791 pressure photoionization mass spectrometry detection, *J. Chromatogr. A.* 1217 (2010) 1950–
792 1955. doi:10.1016/j.chroma.2010.01.071.
- 793 [38] Y. Dohta, T. Yamashita, S. Horiike, T. Nakamura, T. Fukami, A system for LogD screening of
794 96-well plates using a water-plug aspiration/injection method combined with high-performance
795 liquid chromatography-mass spectrometry, *Anal. Chem.* 79 (2007) 8312–8315.
796 doi:10.1021/ac0709798.
- 797 [39] B. Lin, J. Pease, A Novel Method for High Throughput Lipophilicity Determination by
798 Microscale Shake Flask and Liquid Chromatography Tandem Mass Spectrometry, *Comb.*
799 *Chem. High Throughput Screen.* 16 (2013) 817–825. doi:10.2174/1386207311301010007.
- 800 [40] L. Saghale, R.C. Hider, A.S. Mostafavi, Comparison of Automated Continuous Flow Method
801 With Shake- Flask Method in Determining Partition Coefficients of Bidentate
802 Hydroxypyridinone Ligands, *DARU J. Pharm. Sci.* 11 (2003) 38–46.
- 803 [41] H. Cumming, C. Rücker, Octanol–Water Partition Coefficient Measurement by a Simple ¹ H
804 NMR Method, *ACS Omega.* 2 (2017) 6244–6249. doi:10.1021/acsomega.7b01102.
- 805 [42] J. Pawliszyn, *Solid phase microextraction : theory and practice*, Wiley-VCH, 1997.
- 806 [43] C.L. Arthur, L.M. Killam, K.D. Buchholz, J. Pawliszyn, J.R. Berg, Automation and optimization
807 of solid-phase microextraction, *Anal. Chem.* 64 (1992) 1960–1966. doi:10.1021/ac00041a034.
- 808 [44] M. Chai, C.L. Arthur, J. Pawliszyn, R.P. Belardi, K.F. Pratt, Determination of volatile

- 809 chlorinated hydrocarbons in air and water with solid-phase microextraction, *Analyst*. 118
810 (1993) 1501–1505. doi:10.1039/an9931801501.
- 811 [45] C.L. Arthur, L.M. Killam, S. Motlagh, M. Lim, D.W. Potter, J. Pawliszyn, Analysis of substituted
812 benzene compounds in groundwater using solid-phase microextraction, *Environ. Sci. Technol.*
813 26 (1992) 979–983. doi:10.1021/es00029a017.
- 814 [46] D. Louch, S. Motlagh, J. Pawliszyn, Dynamics of organic compound extraction from water
815 using liquid-coated fused silica fibers, *Anal. Chem.* 64 (1992) 1187–1199.
816 doi:10.1021/ac00034a020.
- 817 [47] J.R. Dean, W.R. Tomlinson, V. Makovskaya, R. Cumming, M. Hetheridge, M. Comber, Solid-
818 Phase Microextraction as a Method for Estimating the Octanol–Water Partition Coefficient,
819 *Anal. Chem.* 68 (1996) 130–133. doi:10.1021/ac950778g.
- 820 [48] K.-P. Chao, Y.-T. Lu, H.-W. Yang, Prediction of partition coefficients of organic compounds
821 between SPME/PDMS and aqueous solution., *Int. J. Mol. Sci.* 15 (2014) 2585–95.
822 doi:10.3390/ijms15022585.
- 823 [49] T. Kumazawa, X.-P. Lee, K. Sato, O. Suzuki, Solid-phase microextraction and liquid
824 chromatography/mass spectrometry in drug analysis, *Anal. Chim. Acta.* 492 (2003) 49–67.
825 doi:10.1016/S0003-2670(03)00680-9.
- 826 [50] M. Kah, C.D. Brown, Log D: Lipophilicity for ionisable compounds, *Chemosphere*. 72 (2008)
827 1401–1408. doi:10.1016/J.CHEMOSPHERE.2008.04.074.
- 828 [51] D.N. Brooke, A.J. Dobbs, N. Williams, Octanol:water partition coefficients (P): measurement,
829 estimation, and interpretation, particularly for chemicals with P greater than 10(5)., *Ecotoxicol.*
830 *Environ. Saf.* 11 (1986) 251–60. doi:10.1016/0147-6513(86)90099-0.
- 831 [52] J. De Bruijn, F. Busser, W. Seinen, J. Hermens, Determination of octanol/water partition
832 coefficients for hydrophobic organic chemicals with the “slow-stirring” method, *Environ.*
833 *Toxicol. Chem.* 8 (1989) 499–512. doi:10.1002/etc.5620080607.
- 834 [53] A. Avdeef, Absorption and drug development: solubility, permeability, and charge state, John
835 Wiley & Sons, 2012.
- 836 [54] S.H. Unger, G.H. Chiang, Octanol-Physiological Buffer Distribution Coefficients of Lipophilic
837 Amines by Reversed-Phase High-Performance Liquid Chromatography and Their Correlation
838 with Biological Activity, *J. Med. Chem.* 24 (1981) 262–270.
- 839 [55] A. Hulshoff, J.H. Perrin, A reversed-phase thin-layer chromatographic method for the
840 determination of relative partition coefficients of very lipophilic compounds, *J. Chromatogr. A.*
841 120 (1976) 65–80. doi:10.1016/S0021-9673(01)98998-8.
- 842 [56] J. Sherma, B. Fried, Handbook of thin-layer chromatography, Marcel Dekker, 2003.
- 843 [57] E.C. Bate-Smith, R.G. Westall, Chromatographic behaviour and chemical structure I. Some
844 naturally occurring phenolic substances, *Biochim. Biophys. Acta.* 4 (1950) 427–440.
845 doi:10.1016/0006-3002(50)90049-7.
- 846 [58] E. Soczewiński, C.A. Wachtmeister, The relation between the composition of certain ternary
847 two-phase solvent systems and RM values, *J. Chromatogr. A.* 7 (1962) 311–320.
848 doi:10.1016/S0021-9673(01)86422-0.
- 849 [59] K. Ciura, S. Dziomba, J. Nowakowska, M.J. Markuszewski, Thin layer chromatography in drug
850 discovery process, *J. Chromatogr. A.* 1520 (2017) 9–22.
851 doi:10.1016/J.CHROMA.2017.09.015.
- 852 [60] M. Janicka, K. Stępnik, A. Pachuta-Stec, Quantification of Lipophilicity of 1,2,4-Triazoles Using
853 Micellar Chromatography, *Chromatographia.* 75 (2012) 449–456. doi:10.1007/s10337-012-
854 2227-3.

- 855 [61] K.E. Stępnik, I. Malinowska, E. Rój, *in vitro* and *in silico* determination of oral, jejunum and
856 Caco-2 human absorption of fatty acids and polyphenols. *Micellar liquid chromatography*,
857 *Talanta*. 130 (2014) 265–273. doi:10.1016/J.TALANTA.2014.06.039.
- 858 [62] K. Ciura, M. Belka, P. Kawczak, T. Bączek, J. Nowakowska, The comparative study of micellar
859 TLC and RP-TLC as potential tools for lipophilicity assessment based on QSRR approach, *J.*
860 *Pharm. Biomed. Anal.* 149 (2018) 70–79. doi:10.1016/J.JPBA.2017.10.034.
- 861 [63] M. Janicka, D. Pietras-Ożga, Chromatographic evaluation of the lipophilicity of *N* -
862 phenyltrichloroacetamide derivatives using micellar TLC and OPLC, *J. Planar Chromatogr. –*
863 *Mod. TLC*. 23 (2010) 396–399. doi:10.1556/JPC.23.2010.6.2.
- 864 [64] M.J. Ruiz-Ángel, S. Carda-Broch, J.R. Torres-Lapasió, M.C. García-Álvarez-Coque, Retention
865 mechanisms in micellar liquid chromatography, *J. Chromatogr. A*. 1216 (2009) 1798–1814.
866 doi:10.1016/J.CHROMA.2008.09.053.
- 867 [65] T. Braumann, Determination of hydrophobic parameters by reversed-phase liquid
868 chromatography: theory, experimental techniques, and application in studies on quantitative
869 structure-activity relationships, *J. Chromatogr. A*. 373 (1986) 191–225. doi:10.1016/S0021-
870 9673(00)80213-7.
- 871 [66] W.J. Lambert, Modeling oil-water partitioning and membrane permeation using reversed-
872 phase chromatography, *J. Chromatogr. A*. 656 (1993) 469–484. doi:10.1016/0021-
873 9673(93)80814-O.
- 874 [67] C. Liang, H. Lian, Recent advances in lipophilicity measurement by reversed-phase high-
875 performance liquid chromatography, *Trends Anal. Chem.* 68 (2015) 28–36.
876 doi:10.1016/j.trac.2015.02.009.
- 877 [68] K. Valkó, Application of high-performance liquid chromatography based measurements of
878 lipophilicity to model biological distribution, *J. Chromatogr. A*. 1037 (2004) 299–310.
879 doi:10.1016/j.chroma.2003.10.084.
- 880 [69] OECD, Guideline for Testing of Chemicals, no. 117: Partition Coefficient (n-octanol/water),
881 High Performance Liquid Chromatography Method, 1986 (1989) 1–11.
- 882 [70] K. Valko, C. Du, C. Bevan, D. Reynolds, M. Abraham, Rapid method for the estimation of
883 octanol/water partition coefficient (Log P_{oct}) from gradient RP-HPLC retention and a hydrogen
884 bond acidity term, *Curr. Med. Chem.* 24 (2001) 1137–1146. doi:10.1081/JLC-100103400.
- 885 [71] C. Stella, A. Galland, X. Liu, B. Testa, S. Rudaz, J.L. Veuthey, P.A. Carrupt, Novel RPLC
886 stationary phases for lipophilicity measurement: Solvatochromic analysis of retention
887 mechanisms for neutral and basic compounds, *J. Sep. Sci.* 28 (2005) 2350–2362.
888 doi:10.1002/jssc.200500104.
- 889 [72] E. Lesellier, C. West, A. Tchaplá, Classification of special octadecyl-bonded phases by the
890 carotenoid test, *J. Chromatogr. A*. 1111 (2006) 62–70. doi:10.1016/j.chroma.2006.01.107.
- 891 [73] K. Valko, S. Nunhuck, C. Bevan, M.H. Abraham, D.P. Reynolds, Fast gradient HPLC method
892 to determine compounds binding to human serum albumin. Relationship with octanol water and
893 immobilized artificial membrane lipophilicity, *J. Pharm. Sci.* 92 (2003) 2236–2248.
894 doi:10.1002/jps.10494.
- 895 [74] Ł. Kubik, W. Struck-Lewicka, R. Kaliszan, P. Wiczling, Simultaneous determination of
896 hydrophobicity and dissociation constant for a large set of compounds by gradient reverse
897 phase high performance liquid chromatography-mass spectrometry technique, *J. Chromatogr.*
898 *A*. 1416 (2015) 31–37. doi:10.1016/j.chroma.2015.09.003.
- 899 [75] R. Kaliszan, Quantitative structure-(chromatographic) retention relationships, *Chem. Rev.* 107
900 (2007) 3212–3246. doi:10.1021/cr068412z.
- 901 [76] C. Giaginis, A. Tsantili-Kakoulidou, Alternative measures of lipophilicity: from octanol–water

- 902 partitioning to IAM retention, *J. Pharm. Sci.* 97 (2008) 2984–3004. doi:10.1002/JPS.21244.
- 903 [77] B. Zheng, L.M. West, Estimating the lipophilicity of natural products using a polymeric reversed
904 phase HPLC method, *J. Liq. Chromatogr. Relat. Technol.* 33 (2009) 118–132.
905 doi:10.1080/10826070903430464.
- 906 [78] R. Kaliszan, High performance liquid chromatographic methods and procedures of
907 hydrophobicity determination, *Quant. Struct.-Act. Relat.* 9 (1990) 83–87.
908 doi:10.1002/qsar.19900090202.
- 909 [79] A. Méndez, E. Bosch, M. Rosés, U.D. Neue, Comparison of the acidity of residual silanol
910 groups in several liquid chromatography columns, *J. Chromatogr. A.* 986 (2003) 33–44.
911 doi:10.1016/S0021-9673(02)01899-X.
- 912 [80] V. Pliška, B. Testa, H. van de Waterbeemd, *Lipophilicity in Drug Action and Toxicology*, VCH
913 Publisher, Weinheim, 1996. doi:10.1002/9783527614998.
- 914 [81] B. Sethi, M. Soni, S. Kumar, G.D. Gupta, S. Mishra, R. Singh, Lipophilicity measurement
915 through newer techniques, *J. Pharm. Res.* 3 (2010) 345–351.
- 916 [82] C. Giaginis, A. Tsantili-Kakoulidou, Current state of the art in HPLC methodology for
917 lipophilicity assessment of basic drugs. A review, *J. Liq. Chromatogr. Relat. Technol.* 31
918 (2008) 79–96. doi:10.1080/10826070701665626.
- 919 [83] R.S. Ward, J. Davies, G. Hodges, D.W. Roberts, Applications of immobilised artificial
920 membrane chromatography to quaternary alkylammonium sulfobetaines and comparison of
921 chromatographic methods for estimating the octanol–water partition coefficient, 1007 (2003)
922 67–75. doi:10.1016/S0021-9673(03)00947-6.
- 923 [84] F. Lombardo, M.Y. Shalaeva, K.A. Tupper, F. Gao, ElogDoct: A tool for lipophilicity
924 determination in drug discovery. 2. Basic and neutral compounds, *J. Med. Chem.* 44 (2001)
925 2490–2497. doi:10.1021/jm0100990.
- 926 [85] D. Benhaim, E. Grushka, Characterization of the Gemini C18TM column: Lipophilicity
927 measurement and LSER, *J. Liq. Chromatogr. Relat. Technol.* 31 (2008) 2198–2218.
928 doi:10.1080/10826070802279202.
- 929 [86] D. Benhaim, E. Grushka, Effect of n-octanol in the mobile phase on lipophilicity determination
930 by reversed-phase high-performance liquid chromatography on a modified silica column, *J.*
931 *Chromatogr. A.* 1209 (2008) 111–119. doi:10.1016/j.chroma.2008.08.118.
- 932 [87] C. Liang, J. Qiao, H. Lian, Determination of reversed-phase high performance liquid
933 chromatography based octanol-water partition coefficients for neutral and ionizable
934 compounds: Methodology evaluation, *J. Chromatogr. A.* 1528 (2017) 1–16.
935 doi:10.1016/j.chroma.2017.10.064.
- 936 [88] X. Liu, H. Tanaka, A. Yamauchi, B. Testa, H. Chuman, Lipophilicity measurement by reversed-
937 phase high-performance liquid chromatography (RP-HPLC): A comparison of two stationary
938 phases based on retention mechanisms, *Helv. Chim. Acta.* 87 (2004) 2866–2876.
939 doi:10.1002/hlca.200490258.
- 940 [89] N. Gulyaeva, A. Zaslavsky, P. Lechner, M. Chlenov, A. Chait, B. Zaslavsky, Relative
941 hydrophobicity and lipophilicity of β -blockers and related compounds as measured by aqueous
942 two-phase partitioning, octanol – buffer partitioning, and HPLC, *Eur. J. Pharm. Sci.* 17 (2002)
943 81–93. doi:10.1016/S0928-0987(02)00146-X.
- 944 [90] S.F. Donovan, M.C. Pescatore, Method for measuring the logarithm of the octanol-water
945 partition coefficient by using short octadecyl-poly(vinyl alcohol) high-performance liquid
946 chromatography columns, *J. Chromatogr. A.* 952 (2002) 47–61. doi:10.1016/S0021-
947 9673(02)00064-X.
- 948 [91] F. Barbato, C. Carpentiero, L. Grumetto, M.I. La Rotonda, Enantioselective retention of β -

- 949 blocking agents on human serum albumin and α 1-acid glycoprotein HPLC columns:
950 Relationships with different scales of lipophilicity, *Eur. J. Pharm. Sci.* 38 (2009) 472–478.
951 doi:10.1016/j.ejps.2009.09.011.
- 952 [92] D.S. Hage, J. Austin, High-performance affinity chromatography and immobilized serum
953 albumin as probes for drug- and hormone-protein binding, *J. Chromatogr. B.* 739 (2000) 39–
954 54. doi:10.1016/S0378-4347(99)00445-4.
- 955 [93] A. Taillardat-Bertschinger, P.A. Carrupt, F. Barbato, B. Testa, Immobilized artificial membrane
956 HPLC in drug research, *J. Med. Chem.* 46 (2003) 655–665. doi:10.1021/jm020265j.
- 957 [94] B.H. Stewart, O.H. Chan, Use of immobilized artificial membrane chromatography for drug
958 transport applications, *J. Pharm. Sci.* 87 (1998) 1471–1478. doi:10.1021/js980262n.
- 959 [95] C. Pidgeon, S. Ong, H. Liu, X. Qiu, M. Pidgeon, A.H. Dantzig, J. Munroe, W.J. Hornback, J.S.
960 Kasher, L. Glunz, T. Szczerba, IAM chromatography: an in vitro screen for predicting drug
961 membrane permeability, *J. Med. Chem.* 38 (1995) 590–594. doi:10.1021/jm00004a004.
- 962 [96] E.S. Gallagher, E. Mansfield, C.A. Aspinwall, Stabilized phospholipid membranes in
963 chromatography: toward membrane protein-functionalized stationary phases, *Anal. Bioanal.*
964 *Chem.* 406 (2014) 2223–2229. doi:10.1007/s00216-013-7545-2.
- 965 [97] F. Tsopelas, T. Vallianatou, A. Tsantili-Kakoulidou, The potential of immobilized artificial
966 membrane chromatography to predict human oral absorption, *Eur. J. Pharm. Sci.* 81 (2016)
967 82–93. doi:10.1016/j.ejps.2015.09.020.
- 968 [98] F. Barbato, G. Di Martino, L. Grumetto, M.I. La Rotonda, Prediction of drug-membrane
969 interactions by IAM-HPLC: Effects of different phospholipid stationary phases on the partition
970 of bases, *Eur. J. Pharm. Sci.* 22 (2004) 261–269. doi:10.1016/j.ejps.2004.03.019.
- 971 [99] F. Barbato, The use of immobilised artificial membrane (IAM) chromatography for
972 determination of lipophilicity, *Curr. Comput. Aided. Drug Des.* 2 (2006) 341–352.
973 doi:10.2174/157340906778992319.
- 974 [100] S. Bocian, B. Buszewski, Comparison of retention properties of stationary phases imitated cell
975 membrane in RP HPLC, *J. Chromatogr. B.* 990 (2015) 198–202.
976 doi:10.1016/j.jchromb.2015.03.033.
- 977 [101] K. Valko, C.M. Du, C.D. Bevan, D.P. Reynolds, M.H. Abraham, Rapid-gradient HPLC method
978 for measuring drug interactions with immobilised artificial membrane: comparison with other
979 lipophilicity measures, *J. Pharm. Sci.* 89 (2000) 1085–1095. doi:10.1002/1520-
980 6017(200008)89:8<1085::AID-JPS13>3.0.CO;2-N.
- 981 [102] K.L. Valko, S.P. Teague, C. Pidgeon, In vitro membrane binding and protein binding (IAM
982 MB/PB technology) to estimate in vivo distribution: applications in early drug discovery,
983 *ADMET DMPK.* 5 (2017) 14–38. doi:10.5599/admet.5.1.373.
- 984 [103] Z. Qi, S. Han, Z. Wu, F. Chen, X. Cao, H. Lian, L. Mao, Retention prediction and
985 hydrophobicity measurement of weakly basic compounds in reversed-phase liquid
986 chromatography using ammonia and triethylamine as ion-suppressors, *Curr. Anal. Chem.* 10
987 (2013) 172–181. doi:10.2174/1573411011410010016.
- 988 [104] S.-Y. Han, X. Ming, Z.-C. Qi, D. Sheng, H.-Z. Lian, Retention prediction and hydrophobicity
989 estimation of weak acidic compounds by reversed-phase liquid chromatography using acetic
990 and perchloric acids as ion suppressors, *Anal. Bioanal. Chem.* 398 (2010) 2731–2743.
991 doi:10.1007/s00216-010-4173-y.
- 992 [105] J.J. Fernández-Navarro, J.R. Torres-Lapasió, M.J. Ruiz-Ángel, M.C. García-Álvarez-Coque, 1-
993 Hexyl-3-methyl imidazolium tetrafluoroborate: An efficient column enhancer for the separation
994 of basic drugs by reversed-phase liquid chromatography, *J. Chromatogr. A.* 1258 (2012) 168–
995 174. doi:10.1016/j.chroma.2012.08.051.

- 996 [106] R. Kaliszan, M.P. Marszał, M.J. Markuszewski, T. Bączek, J. Pernak, Suppression of
997 deleterious effects of free silanols in liquid chromatography by imidazolium tetrafluoroborate
998 ionic liquids, *J. Chromatogr. A.* 1030 (2004) 263–271. doi:10.1016/j.chroma.2003.09.020.
- 999 [107] C. Giaginis, S. Theocharis, A. Tsantili-Kakoulidou, Octanol/water partitioning simulation by
1000 reversed-phase high performance liquid chromatography for structurally diverse acidic drugs:
1001 Effect of n-octanol as mobile phase additive, *J. Chromatogr. A.* 1166 (2007) 116–125.
1002 doi:10.1016/j.chroma.2007.08.004.
- 1003 [108] A. Pyka, A. Kazimierczak, D. Gurak, Utilization of reversed-phase TLC and topological indices
1004 to the lipophilicity investigations of naproxen, *Pharm. Methods.* 4 (2013) 16–20.
1005 doi:10.1016/J.PHME.2013.05.001.
- 1006 [109] M. Dąbrowska, M. Starek, Ł. Komsta, P. Szafranski, A. Stasiewicz-Urban, W. Opoka,
1007 Assessment of the chromatographic lipophilicity of eight cephalosporins on different stationary
1008 phases, *Eur. J. Pharm. Sci.* 101 (2017) 115–124. doi:10.1016/J.EJPS.2017.01.034.
- 1009 [110] A.H. Rageh, N.N. Atia, H.M. Abdel-Rahman, Lipophilicity estimation of statins as a decisive
1010 physicochemical parameter for their hepato-selectivity using reversed-phase thin layer
1011 chromatography, *J. Pharm. Biomed. Anal.* 142 (2017) 7–14. doi:10.1016/J.JPBA.2017.04.037.
- 1012 [111] S.C. Cobzac, D. Casoni, C. Sarbu, Lipophilicity of Amine Neurotransmitter Precursors,
1013 Metabolites and Related Drugs Estimated on Various TLC Plates, *J. Chromatogr. Sci.* 52
1014 (2014) 1095–1103. doi:10.1093/chromsci/bmt155.
- 1015 [112] U. Hubicka, B. Żuromska-Witek, Ł. Komsta, J. Krzek, Lipophilicity study of fifteen
1016 fluoroquinolones by reversed-phase thin-layer chromatography, *Anal. Methods.* 7 (2015)
1017 3841–3848. doi:10.1039/C4AY02203C.
- 1018 [113] C. Onişor, M. Poşa, S. Kevrešan, K. Kuhajda, C. Sârbu, Estimation of chromatographic
1019 lipophilicity of bile acids and their derivatives by reversed-phase thin layer chromatography, *J.*
1020 *Sep. Sci.* 33 (2010) 3110–3118. doi:10.1002/jssc.200900879.
- 1021 [114] S. Šegan, I. Opsenica, M. Zlatović, D. Milojković-Opsenica, B. Šolaja, Quantitative structure
1022 retention/activity relationships of biologically relevant 4-amino-7-chloroquinoline based
1023 compounds, *J. Chromatogr. B.* 1012–1013 (2016) 144–152.
1024 doi:10.1016/J.JCHROMB.2016.01.033.
- 1025 [115] C. Eadsforth, C. Adams, T. Austin, T. Corry, S. Forbes, S. Harris, Validation of an HPLC
1026 method for determining log Pow values of surfactants, *Tenside Surf. Det.* 51 (2014) 230–239.
1027 doi:10.3139/113.110303.
- 1028 [116] M. Grover, M. Gulati, B. Singh, S. Singh, RP-HPLC determination of lipophilicity of 22
1029 penicillins, their correlation with reported values and establishment of quantitative structure-log
1030 Kw relationships, *QSAR Comb. Sci.* 24 (2005) 639–648. doi:10.1002/qsar.200430902.
- 1031 [117] S.K. Sahu, G.G. Pandit, Estimation of octanol-water partition coefficients for polycyclic aromatic
1032 hydrocarbons using reverse-phase HPLC, *J. Liq. Chromatogr. Relat. Technol.* 26 (2003) 135–
1033 146. doi:10.1081/JLC-120017158.
- 1034 [118] S. Griffin, S.G. Wyllie, J. Markham, Determination of octanol-water partition coefficient for
1035 terpenoids using reversed-phase high-performance liquid chromatography, *J. Chromatogr. A.*
1036 864 (1999) 221–228. doi:10.1016/S0021-9673(99)01009-2.
- 1037 [119] S. Han, J. Qiao, Y. Zhang, L. Yang, H. Lian, X. Ge, H. Chen, Determination of n-octanol/water
1038 partition coefficient for DDT-related compounds by RP-HPLC with a novel dual-point retention
1039 time correction, *Chemosphere.* 83 (2011) 131–136. doi:10.1016/j.chemosphere.2011.01.013.
- 1040 [120] P. Wiczling, W. Struck-Lewicka, Kubik, D. Siluk, M.J. Markuszewski, R. Kaliszan, The
1041 simultaneous determination of hydrophobicity and dissociation constant by liquid
1042 chromatography-mass spectrometry, *J. Pharm. Biomed. Anal.* 94 (2014) 180–187.
1043 doi:10.1016/j.jpba.2014.01.038.



- 1044 [121] I.A. Sima, A. Kot-Wasik, A. Wasik, J. Namieśnik, C. Sârbu, Assessment of lipophilicity indices
1045 derived from retention behavior of antioxidant compounds in RP-HPLC, *Molecules*. 22 (2017)
1046 1–9. doi:10.3390/molecules22040550.
- 1047 [122] M. Koba, M. Belka, T. Ciesielski, T. Bączek, Determination of lipophilicity for antitumor
1048 acridinone derivatives supported by gradient high-performance liquid chromatography method,
1049 *Cent. Eur. J. Chem.* 10 (2012) 216–223. doi:10.2478/s11532-011-0131-6.
- 1050 [123] C. Sârbu, R. Domnica, N. Cu-Briciu, D. Casoni, A. Kot-Wasik, A. Wasik, J. Namieśnik,
1051 Chromatographic lipophilicity determination using large volume injections of the solvents non-
1052 miscible with the mobile phase, *J. Chromatogr. A*. 1266 (2012) 53–60.
1053 doi:10.1016/j.chroma.2012.10.007.
- 1054 [124] D.P. Nowotnik, T. Feld, A.D. Nunn, Examination of some reversed-phase high-performance
1055 liquid chromatography systems for the determination of lipophilicity, *J. Chromatogr.* 630 (1993)
1056 105–115. doi:10.1016/0021-9673(93)80445-E.
- 1057 [125] W.J. Lambert, L.A. Wright, J.K. Stevens, Development of a preformulation lipophilicity screen
1058 utilizing a C-18-derivatized polystyrene-divinylbenzene high-performance liquid
1059 chromatographic (HPLC) column, *Pharm. Res.* 7 (1990) 577–586.
1060 doi:10.1023/A:1015857925630.
- 1061 [126] S. Rezaee, a Khalaj, N. Adibpour, M. Saffary, Correlation between lipophilicity and
1062 antimicrobial activity of some 2-(4-substituted phenyl)-3 (2H)-isothiazolones, *DARU J. Pharm.*
1063 *Sci.* 17 (2009) 256–263.
- 1064 [127] G. Ermondi, F. Catalano, M. Vallaro, I. Ermondi, M.P. Camacho Leal, L. Rinaldi, S. Visentin,
1065 G. Caron, Lipophilicity of amyloid β -peptide 12-28 and 25-35 to unravel their ability to promote
1066 hydrophobic and electrostatic interactions, *Int. J. Pharm.* 495 (2015) 179–185.
1067 doi:10.1016/j.ijpharm.2015.08.075.
- 1068 [128] G. Caron, M. Vallaro, G. Ermondi, G.H. Goetz, Y.A. Abramov, L. Philippe, M. Shalaeva, A fast
1069 chromatographic method for estimating lipophilicity and ionization in nonpolar membrane-like
1070 environment, *Mol. Pharm.* 13 (2016) 1100–1110. doi:10.1021/acs.molpharmaceut.5b00910.
- 1071 [129] M. Iljaš, I. Malnar, V. Gabelica Marković, V. Stepanić, Study of lipophilicity and membrane
1072 partition of 4-hydroxycoumarins by HPLC and PCA, *J. Pharm. Biomed. Anal.* 76 (2013) 104–
1073 111. doi:10.1016/j.jpba.2012.11.043.
- 1074 [130] F. Barbato, V. Cirocco, L. Grumetto, M. Immacolata La Rotonda, Comparison between
1075 immobilized artificial membrane (IAM) HPLC data and lipophilicity in n-octanol for quinolone
1076 antibacterial agents, *Eur. J. Pharm. Sci.* 31 (2007) 288–297. doi:10.1016/j.ejps.2007.04.003.
- 1077 [131] F. Tsopelas, A. Tsantili-Kakoulidou, M. Ochsenkühn-Petropoulou, Biomimetic chromatographic
1078 analysis of selenium species: Application for the estimation of their pharmacokinetic
1079 properties, *Anal. Bioanal. Chem.* 397 (2010) 2171–2180. doi:10.1007/s00216-010-3624-9.
- 1080 [132] M. Chrysanthakopoulos, C. Giaginis, A. Tsantili-Kakoulidou, Retention of structurally diverse
1081 drugs in human serum albumin chromatography and its potential to simulate plasma protein
1082 binding, *J. Chromatogr. A*. 1217 (2010) 5761–5768. doi:10.1016/j.chroma.2010.07.023.
- 1083 [133] L. Grumetto, C. Carpentiero, F. Barbato, Lipophilic and electrostatic forces encoded in IAM-
1084 HPLC indexes of basic drugs: Their role in membrane partition and their relationships with
1085 BBB passage data, *Eur. J. Pharm. Sci.* 45 (2012) 685–692. doi:10.1016/j.ejps.2012.01.008.
- 1086 [134] F. Pehourcq, C. Jarry, B. Bannwarth, Potential of immobilized artificial membrane
1087 chromatography for lipophilicity determination of arylpropionic acid non-steroidal anti-
1088 inflammatory drugs, *J. Pharm. Biomed. Anal.* 33 (2003) 137–144. doi:10.1016/S0731-
1089 7085(03)00257-7.
- 1090 [135] S.T.J. Droge, J.L.M. Hermens, S. Gutsell, J. Rabone, G. Hodges, Predicting the
1091 phospholipophilicity of monoprotic positively charged amines, *Environ. Sci. Process. Impacts*.

- 1092 19 (2017) 307–323. doi:10.1039/C6EM00615A.
- 1093 [136] K. Valkó, L.R. Snyder, J.L. Glajch, Retention in reversed-phase liquid chromatography as a
1094 function of mobile-phase composition, *J. Chromatogr. A.* 656 (1993) 501–520.
1095 doi:10.1016/0021-9673(93)80816-Q.
- 1096 [137] S. Han, C. Liang, J. Qiao, H. Lian, X. Ge, H. Chen, A novel evaluation method for extrapolated
1097 retention factor in determination of n -octanol/water partition coefficient of halogenated organic
1098 pollutants by reversed-phase high performance liquid chromatography, *Anal. Chim. Acta.* 713
1099 (2012) 130–135. doi:10.1016/j.aca.2011.11.020.
- 1100 [138] K. Valkó, C. Bevan, D. Reynolds, Chromatographic hydrophobicity index by fast-gradient RP-
1101 HPLC: A high-throughput alternative to log P/log D, *Anal. Chem.* 69 (1997) 2022–2029.
1102 doi:10.1021/ac961242d.
- 1103 [139] K. Valkó, P. Slégel, New chromatographic hydrophobicity index (ϕ_0) based on the slope and
1104 the intercept of the log k' versus organic phase concentration plot, *J. Chromatogr. A.* 631
1105 (1993) 49–61. doi:10.1016/0021-9673(93)80506-4.
- 1106 [140] J.D. Krass, B. Jastorff, H.G. Genieser, Determination of lipophilicity by gradient elution high-
1107 performance liquid chromatography, *Anal. Chem.* 69 (1997) 2575–81. doi:10.1021/ac961246i.
- 1108 [141] G. Camurri, A. Zaramella, High-throughput liquid chromatography/mass spectrometry method
1109 for the determination of the chromatographic hydrophobicity index, *Anal. Chem.* 73 (2001)
1110 3716–3722. doi:10.1021/ac001388j.
- 1111 [142] P. Wiczling, M.J. Markuszewski, M. Kaliszan, R. Kaliszan, pH/organic solvent double-gradient
1112 reversed-phase HPLC, *Anal. Chem.* 77 (2005) 449–458. doi:10.1021/ac049092r.
- 1113 [143] R.L.C. Voeten, I.K. Ventouri, R. Haselberg, G.W. Somsen, Capillary Electrophoresis: Trends
1114 and Recent Advances, *Anal. Chem.* 90 (2018) 1464–1481.
1115 doi:10.1021/acs.analchem.8b00015.
- 1116 [144] S. El Deeb, H. Wätzig, D. Abd El-Hady, C. Sängler-van de Griend, G.K.E. Scriba, Recent
1117 advances in capillary electrophoretic migration techniques for pharmaceutical analysis (2013-
1118 2015), *Electrophoresis.* 37 (2016) 1591–1608. doi:10.1002/elps.201600058.
- 1119 [145] D. Erickson, Electroosmotic Flow (DC), in: *Encycl. Microfluid. Nanofluidics*, Springer US,
1120 Boston, MA, 2014: pp. 1–11. doi:10.1007/978-3-642-27758-0_446-2.
- 1121 [146] S. Kanchi, S. Sagrado, M.I. Sabela, K. Bisetty, Capillary Electrophoresis: Trends and
1122 Developments in Pharmaceutical Research, Pan Stanford Publishing Pte. Ltd., USA, 2017.
1123 doi:10.4032/9781315225388.
- 1124 [147] D.A. Skoog, F.J. Holler, S.R. Crouch, Principles of instrumental analysis, Brooks Cole, 2007.
- 1125 [148] V. Mantovani, F. Galeotti, F. Maccari, N. Volpi, Recent advances in capillary electrophoresis
1126 separation of monosaccharides, oligosaccharides, and polysaccharides, *Electrophoresis.* 39
1127 (2018) 179–189. doi:10.1002/elps.201700290.
- 1128 [149] V. Kašička, Recent developments in capillary and microchip electroseparations of peptides
1129 (2015-mid 2017), *Electrophoresis.* 39 (2018) 209–234. doi:10.1002/elps.201700295.
- 1130 [150] K.-S. Wong, J. Kenseth, R. Strasburg, Validation and long-term assessment of an approach
1131 for the high throughput determination of lipophilicity (logPOW) values using multiplexed,
1132 absorbance-based capillary electrophoresis, *J. Pharm. Sci.* 93 (2004) 916–931.
1133 doi:10.1002/jps.20011.
- 1134 [151] S. Terabe, Capillary Separation: Micellar Electrokinetic Chromatography, *Annu. Rev. Anal.*
1135 *Chem.* 2 (2009) 99–120. doi:10.1146/annurev.anchem.1.031207.113005.
- 1136 [152] M. Silva, Micellar electrokinetic chromatography: A review of methodological and instrumental

- 1137 innovations focusing on practical aspects, *Electrophoresis*. 34 (2013) 141–158.
1138 doi:10.1002/elps.201200349.
- 1139 [153] W.A. Wan Ibrahim, D. Hermawan, M.N. Hasan, H.Y. Aboul Enein, M.M. Sanagi, Rapid
1140 Estimation of Octanol–Water Partition Coefficient for Triazole Fungicides by MEKC with
1141 Sodium Deoxycholate as Surfactant, *Chromatographia*. 68 (2008) 415–419.
1142 doi:10.1365/s10337-008-0721-4.
- 1143 [154] J. Østergaard, Application of retention factors in affinity electrokinetic chromatography and
1144 capillary electrophoresis., *Anal. Sci.* 23 (2007) 489–92. doi:10.2116/analsci.23.489.
- 1145 [155] H. Yang, Y. Ding, J. Cao, P. Li, Twenty-one years of microemulsion electrokinetic
1146 chromatography (1991-2012): A powerful analytical tool, *Electrophoresis*. 34 (2013) 1273–
1147 1294. doi:10.1002/elps.201200494.
- 1148 [156] R. Ryan, K. Altria, E. McEvoy, S. Donegan, J. Power, A review of developments in the
1149 methodology and application of microemulsion electrokinetic chromatography, *Electrophoresis*.
1150 34 (2013) 159–177. doi:10.1002/elps.201200375.
- 1151 [157] Z. Xia, J. Yang, L. Li, F. Yang, X. Jiang, Determination of Octanol–Water Partition Coefficients
1152 by MEEKC Based on Peak-Shift Assay, *Chromatographia*. 72 (2010) 495–501.
1153 doi:10.1365/s10337-010-1666-y.
- 1154 [158] A. Fernández-Pumarega, S. Amézqueta, E. Fuguet, M. Rosés, Feasibility of the estimation of
1155 octanol-water distribution coefficients of acidic drugs by microemulsion electrokinetic
1156 chromatography, *ADMET DMPK*. 6 (2018) 55. doi:10.5599/admet.6.1.510.
- 1157 [159] K. Giringer, H.U. Holtkamp, S. Movassaghi, W.D.J. Tremlett, N.Y.S. Lam, M. Kubanik, C.G.
1158 Hartinger, Analysis of ruthenium anticancer agents by MEEKC-UV and MEEKC-ICP-MS:
1159 Impact of structural motifs on lipophilicity and biological activity, *Electrophoresis*. 39 (2018)
1160 1201–1207. doi:10.1002/elps.201700443.
- 1161 [160] Y. Ishihama, Y. Oda, K. Uchikawa, N. Asakawa, Evaluation of Solute Hydrophobicity by
1162 Microemulsion Electrokinetic Chromatography, *Anal. Chem.* 67 (1995) 1588–1595.
1163 doi:10.1021/ac00105a018.
- 1164 [161] R.J. Pascoe, J.A. Masucci, J.P. Foley, Investigation of vesicle electrokinetic chromatography
1165 as an in vitro assay for the estimation of intestinal permeability of pharmaceutical drug
1166 candidates, *Electrophoresis*. 27 (2006) 793–804. doi:10.1002/elps.200500647.
- 1167 [162] L. Jiang, Y. Cao, X. Ni, M. Zhang, G. Cao, Influences of the concentration and the molar ratio
1168 of mixed surfactants on the performance of vesicle pseudostationary phase, *Electrophoresis*.
1169 39 (2018) 1794–1801. doi:10.1002/elps.201800023.
- 1170 [163] W.L. Klotz, M.R. Schure, J.P. Foley, Rapid estimation of octanol-water partition coefficients
1171 using synthesized vesicles in electrokinetic chromatography, *J. Chromatogr. A*. 962 (2002)
1172 207–219. doi:10.1016/S0021-9673(02)00352-7.
- 1173 [164] M. Hong, B.S. Weekley, S.J. Grieb, J.P. Foley, Electrokinetic chromatography using
1174 thermodynamically stable vesicles and mixed micelles formed from oppositely charged
1175 surfactants, *Anal. Chem.* 70 (1998) 1394–1403. doi:10.1021/ac970730y.
- 1176 [165] Z. Jiang, J. Reilly, B. Everatt, A method for rapidly predicting drug tissue distribution using
1177 surfactant vesicle electrokinetic chromatography, *Electrophoresis*. 29 (2008) 3674–3684.
1178 doi:10.1002/elps.200800236.
- 1179 [166] Fritz Scholz, ed., *Electroanalytical Methods*, Springer, Greifswald, 2009. doi:10.1007/978-3-
1180 642-02915-8.
- 1181 [167] R.A. Scherrer, S.F. Donovan, Automated potentiometric titrations in KCl/water-saturated
1182 octanol: method for quantifying factors influencing ion-pair partitioning., *Anal. Chem.* 81 (2009)
1183 2768–78. doi:10.1021/ac802729k.

- 1184 [168] G. Bouchard, P.A. Carrupt, B. Testa, V. Gobry, H.H. Girault, The apparent lipophilicity of
1185 quaternary ammonium ions is influenced by Galvani potential difference, not ion-pairing: A
1186 cyclic voltammetry study, *Pharm. Res.* 18 (2001) 702–708. doi:10.1023/A:1011001914685.
- 1187 [169] G. Caron, F. Reymond, P.-A. Carrupt, H.H. Girault, B. Testa, Combined molecular lipophilicity
1188 descriptors and their role in understanding intramolecular effects, *Pharm. Sci. Technol.*
1189 *Today.* 2 (1999) 327–335. doi:10.1016/S1461-5347(99)00180-7.
- 1190

ACCEPTED MANUSCRIPT


Fig. 1. Charts that shows the total number of publications by year that include the phrases “lipophilicity” or “lipophilic properties” or “partition coefficient” or “distribution coefficient” or “hydrophobicity” in the title, abstract, keywords or text, as searched through the Web of Science and Scopus databases. The difference in search results may be due to the type of published items that are considered by these search engines (i.e. original papers, reviews, book chapters, conference papers, short survey, etc.).


Fig. 2. Proposed classification of methods of lipophilicity assessment.

Fig. 3. Schematic presentation of direct experimental approaches of lipophilicity determination: a) procedure of the shake-flask method (SFM), b) the water-plug aspiration/injection method, c) modification of SFM based on NMR measurement, d) modification of SFM based on solid phase microextraction [26, 27, 38, 41]





Fig. 4. Partition process of less (white particles) and higher lipophilic (grey particles) compounds between stationary and mobile phases during chromatographic run. The retention factor (k) of compound obtained on the HPLC stationary phase is proportional to its affinity (partition or distribution coefficient; K) to the bonded groups presented on the surface of the column packing material, as depicted in the equations, where n_s and n_m stands for average numbers of molecules in the stationary and mobile phase, respectively, C_s and C_m are the molar concentrations of analyte in the stationary and mobile phase, respectively, V_s and V_m are the volumes of stationary and mobile phase, respectively t_R and t_0 are the retention times of the analyte and the unretained compound, i.e. uracil, thiourea (known as column dead time).


Fig. 5. The thermodynamic cycle of the ionization and partitioning of acid (HA) between *n*-octanol and aqueous phases based on Scherer and Donovan [167]. The pK_a in *n*-octanol (pK_{a_0}) is defined to be equal to the pH of the aqueous phase (0.15M KCl) which is in equilibrium with the partition system when the concentration of acid (HA_0) and anions (A_0^-) in *n*-octanol phase are equal. Hence, the knowledge of pK_{a_0} , partition coefficient of neutral forms of a compound ($\log P^N$) and pK_a in aqueous phase allows to calculate the partition coefficient of the ionized forms ($\log P^I$). When the circle of equilibria is present, the difference between $\log P^N$ and $\log P^I$ is the same as the difference between pK_a values in aqueous and *n*-octanol phases.






ACCEPTED MANUSCRIPT





ACCEPTED MANUSCRIPT





ACCEPTED MANUSCRIPT

- The role of lipophilicity in biological, environmental and technical science.
- Lipophilicity assessment using classical and modern approaches.
- Advantages and limitations of methods of lipophilicity determination.
- Novel solutions in chromatographic methods used for lipophilicity determination.

ACCEPTED MANUSCRIPT